

Title (en)
Mechanical face seals.

Title (de)
Gleitringdichtung.

Title (fr)
Garniture mécanique d'étanchéité.

Publication
EP 0404358 A2 19901227 (EN)

Application
EP 90305663 A 19900524

Priority
GB 8913000 A 19890606

Abstract (en)
A mechanical face seal for providing a seal between a shaft (11) and a housing (16) includes a first seal face member (10) mounted on the shaft (11) in fixed rotational and axial relationship and sealed with respect thereto and a second seal face member (15) mounted in fixed rotational relationship but moveable axially of the housing (16); said second seal face member (15) being sealed with respect to the housing (16) by means of a sealing element (28), the sealing element (28) being located in a groove (25) defined between opposed surfaces (27, 26) of the second seal face member (15) and housing (16), the wall of the groove (25) between the sealing element (28) and the side of the seal exposed to a product being defined by a friction insert (35) slidably mounted on the second seal face member (15) and providing a close clearance (30) with the housing (16).

IPC 1-7
F16J 15/38

IPC 8 full level
F16J 15/34 (2006.01); **F16J 15/38** (2006.01); **F16J 15/447** (2006.01)

CPC (source: EP US)
F16J 15/3464 (2013.01 - EP US); **F16J 15/38** (2013.01 - EP US); **Y10S 277/91** (2013.01 - EP US)

Cited by
CN105283700A; US7001565B2; US10753476B2

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0404358 A2 19901227; **EP 0404358 A3 19910130**; CA 2018225 A1 19901206; GB 2232728 A 19901219; GB 2232728 B 19921209; GB 8913000 D0 19890726; JP H0320176 A 19910129; US 5026076 A 19910625

DOCDB simple family (application)
EP 90305663 A 19900524; CA 2018225 A 19900604; GB 8913000 A 19890606; JP 14556790 A 19900605; US 53243190 A 19900604