

Title (en)

METHOD FOR THERMALLY TOUGHENING GLASS SHEETS AND GLASS SHEETS OBTAINED BY THIS METHOD, IN PARTICULAR TO BE USED AS MOTOR VEHICLE SIDE OR REAR WINDOWS.

Publication

EP 0000269 B1 19801029 (EN)

Application

EP 78300072 A 19780623

Priority

GB 2636277 A 19770623

Abstract (en)

[origin: EP0000269A1] Method for thermally toughening glass sheets and glass sheets obtained by this method, in particular to be used as motor vehicle side or rear windows. <??>A method of thermally toughening glass sheets for use as motor vehicle side or rear windows so that the glass sheets produced conform to regulations specifying fracture requirements. <??>The glass sheets are advanced through a quenching station for gas quenching. The glass is subjected to at least one localised gas flow which is pulsed at a repetition frequency related to the speed or advance of the glass sheet through the quenching station. The method induces in the glass sheet a distribution of regions of more highly toughened glass interspersed with regions of lesser toughened glass.

IPC 1-7

C03B 27/00; B60J 1/08; B60J 1/18

IPC 8 full level

C03B 27/044 (2006.01); **C03B 27/048** (2006.01); **C03B 27/052** (2006.01)

CPC (source: EP US)

C03B 27/0404 (2013.01 - EP US); **C03B 27/0413** (2013.01 - EP US); **C03B 27/0417** (2013.01 - EP US)

Cited by

US5827345A; EP0761613A3; EP1069085A3; FR2553083A1; EP0761612A1; US5782947A; EP0781730A3; US6094943A; GB2128602A

Designated contracting state (EPC)

BE DE FR GB NL

DOCDB simple family (publication)

EP 0000269 A1 19790110; EP 0000269 B1 19801029; DE 2860253 D1 19810129; IE 47521 B1 19840418; IE 781218 L 19781223; IT 1111483 B 19860113; IT 7868473 A0 19780622; JP S5433517 A 19790312; JP S6140608 B2 19860910; US 4182619 A 19800108

DOCDB simple family (application)

EP 78300072 A 19780623; DE 2860253 T 19780623; IE 121878 A 19780616; IT 6847378 A 19780622; JP 7593378 A 19780622; US 91655578 A 19780619