

Title (en)  
CABLE HOIST PULLEY

Publication  
**EP 0000675 B1 19801210 (FR)**

Application  
**EP 78400056 A 19780710**

Priority  
FR 7723696 A 19770727

Abstract (en)  
[origin: ES244803U] Load lifting device, in particular a rig consisting of a support equipped at its rear with an organ for hooking an axle of a movable pulley on this axle and located between the two wings of the support, characterized in that the axle includes at least one fixed sheave arranged outside the support that can cooperate, in the case of use in a descender and/or elevator, with the movable sheave by means of recesses made in the wing of the support interposed between the movable sheave and the sheave (s) fixed that allow the passage of the rope. (Machine-translation by Google Translate, not legally binding)

IPC 1-7  
**B66D 3/10**

IPC 8 full level  
**B66D 3/10** (2006.01); **B66D 5/16** (2006.01)

CPC (source: EP US)  
**B66D 3/10** (2013.01 - EP US); **Y10T 24/3911** (2015.01 - EP US)

Cited by  
CN114044455A

Designated contracting state (EPC)  
BE CH DE GB LU NL SE

DOCDB simple family (publication)  
**EP 0000675 A1 19790207**; **EP 0000675 B1 19801210**; AR 217700 A1 19800415; CA 1102783 A 19810609; DE 2860291 D1 19810219; ES 244803 U 19800301; ES 244803 Y 19800816; FR 2398690 A1 19790223; FR 2398690 B1 19800711; IT 1097384 B 19850831; IT 7826029 A0 19780724; JP S5427160 A 19790301; US 4264056 A 19810428; US 4332372 A 19820601

DOCDB simple family (application)  
**EP 78400056 A 19780710**; AR 27310978 A 19780727; CA 308080 A 19780725; DE 2860291 T 19780710; ES 244803 U 19780727; FR 7723696 A 19770727; IT 2602978 A 19780724; JP 9104078 A 19780727; US 23555281 A 19810218; US 92736478 A 19780724