

Title (en)

ROAD VEHICLE WITH TWO JOINTEDLY CONNECTED VEHICLE PARTS

Publication

EP 0000905 B1 19800820 (DE)

Application

EP 78100641 A 19780810

Priority

DE 2738311 A 19770825

Abstract (en)

[origin: US4168848A] The invention provides a road vehicle having two vehicular sections connected together by an articulation joint having on each side thereof a shock-absorbing or arrester device having a pair of arms adapted to engage each other through an abutment when the two vehicular sections pivot relative to each other in one direction and to become disengaged from each other when the two vehicular sections pivot relative to each other in the other direction. The abutment of each pair of mutually engaging arms has an interlocking profile to prevent lateral movement therebetween, and stop mechanisms are provided to retain each arm when they are disengaged from each other, in such a position that when they next become engaged owing to said vehicular sections pivoting in said one direction, said arms are positioned for interlocking engagement with each other.

IPC 1-7

B60D 7/00

IPC 8 full level

B60D 5/00 (2006.01); **B62D 53/00** (2006.01); **B60D 99/00** (2009.01); **B62D 47/02** (2006.01)

CPC (source: EP US)

B60D 5/00 (2013.01 - EP US); **B62D 47/025** (2013.01 - EP US)

Cited by

WO2011104212A1

Designated contracting state (EPC)

BE CH DE FR NL SE

DOCDB simple family (publication)

EP 0000905 A1 19790307; **EP 0000905 B1 19800820**; BR 7805480 A 19790508; CA 1096898 A 19810303; DE 2738311 A1 19790308; DE 2738311 B2 19790830; DE 2738311 C3 19800522; DE 2860238 D1 19801204; GB 1599577 A 19811007; HU 176106 B 19801228; IT 1103058 B 19851014; IT 7809571 A0 19780822; JP S5445027 A 19790410; US 4168848 A 19790925

DOCDB simple family (application)

EP 78100641 A 19780810; BR 7805480 A 19780824; CA 308440 A 19780731; DE 2738311 A 19770825; DE 2860238 T 19780810; GB 1889778 A 19780511; HU HA001065 A 19780731; IT 957178 A 19780822; JP 10336378 A 19780823; US 93390078 A 19780815