

Title (en)

METHODS OF AND APPARATUS FOR CONTROLLING CAPACITANCE UNBALANCE-TO-GROUND IN CABLES

Publication

EP 0000954 B1 19811021 (EN)

Application

EP 78100780 A 19780830

Priority

US 82936277 A 19770831

Abstract (en)

[origin: EP0000954A2] Capacitance unbalance-to-ground between conductors of a twisted pair, each of which may be insulated with at least a layer of cellular plastic insulation, is maintained within acceptable limits by controlling the extrusion of the insulation to maintain the measured coaxial capacitance and associated outside diameter of the insulated conductors within a range of values which correspond to acceptable capacitance unbalance-to-ground values.

IPC 1-7

H01B 13/06; **H01B 13/14**

IPC 8 full level

G01R 31/02 (2006.01); **H01B 13/06** (2006.01); **H01B 13/14** (2006.01)

CPC (source: EP US)

G01R 31/59 (2020.01 - EP US); **H01B 13/06** (2013.01 - EP US); **H01B 13/14** (2013.01 - EP US)

Cited by

GB2130763A; FR2452136A1; US4592881A

Designated contracting state (EPC)

BE DE FR GB NL SE

DOCDB simple family (publication)

EP 0000954 A2 19790307; **EP 0000954 A3 19790404**; **EP 0000954 B1 19811021**; CA 1105594 A 19810721; DE 2861199 D1 19811224; ES 473000 A1 19790316; IT 1099315 B 19850918; IT 7827163 A0 19780830; JP S5448086 A 19790416; JP S6235208 B2 19870731; US 4174236 A 19791113

DOCDB simple family (application)

EP 78100780 A 19780830; CA 310137 A 19780828; DE 2861199 T 19780830; ES 473000 A 19780831; IT 2716378 A 19780830; JP 10569178 A 19780831; US 82936277 A 19770831