

Title (en)
KEY FASTENING SUPPORT

Publication
EP 0001282 B1 19800917 (DE)

Application
EP 78100934 A 19780919

Priority
DE 2742720 A 19770922

Abstract (en)
[origin: US4198838A] A suspension device for fastening keys onto a carrier member, which comprises a U-shaped holding member connectable to a carrier member and includes two oppositely located legs with two substantially parallel walls defining with each other a longitudinally extending slot. The two legs are interconnected at one end thereof where they define a preferably rounded receiving section wider than the longitudinally extending slot. The device furthermore includes a coupling member detachably connectable to the holding member and having one end provided with a web of substantially rectangular cross section the diagonal of which is shorter than the diameter of the receiving section whereas the narrow sides of the web are shorter and its wider sides are longer than the clear width of the slot, at least the wider sides of the web being inclined relative to the main plane of the coupling member, and the other end of the coupling member being provided with an opening for receiving and holding keys.

IPC 1-7
A45C 5/12; **A47G 29/10**

IPC 8 full level
A45C 11/32 (2006.01); **A45C 13/02** (2006.01)

CPC (source: EP US)
A45C 11/32 (2013.01 - EP US); **A45C 13/023** (2013.01 - EP US); **Y10T 70/8784** (2015.04 - EP US)

Designated contracting state (EPC)
BE CH FR GB LU NL SE

DOCDB simple family (publication)
DE 2742720 B1 19781019; **DE 2742720 C2 19790613**; AT 365903 B 19820225; AT A681378 A 19810715; EP 0001282 A1 19790404; EP 0001282 B1 19800917; US 4198838 A 19800422

DOCDB simple family (application)
DE 2742720 A 19770922; AT 681378 A 19780921; EP 78100934 A 19780919; US 94437178 A 19780921