

Title (en)  
RIBBON CABLE CONNECTOR WITH OPTICAL CONTROL

Publication  
**EP 0002984 B1 19810401 (FR)**

Application  
**EP 78400244 A 19781215**

Priority  
FR 7739772 A 19771230

Abstract (en)  
[origin: US4217022A] Connector with insulation piercing lugs for ribbon cable, in which the connection of each wire of the cable, is achieved by insertion in a slot having cutting edges (13) located on a lug (6) of the connector (1) through the action of a pusher member (14). The pusher member (14) comprises in its upper portion a plurality of magnifying lenses constituted by a single block (41) therewith and enabling accurate visual inspection of each wire insertion process, without any need for disassembly.

IPC 1-7  
**H01R 13/46**; **H01R 4/24**

IPC 8 full level  
**H01R 4/24** (2006.01); **H01R 12/67** (2011.01); **H01R 13/46** (2006.01); **H01R 43/01** (2006.01); **H01R 12/59** (2011.01); **H01R 13/66** (2006.01)

CPC (source: EP US)  
**H01R 12/67** (2013.01 - EP US); **H01R 13/46** (2013.01 - EP US); **H01R 4/242** (2013.01 - EP US); **H01R 12/59** (2013.01 - EP US);  
**H01R 13/66** (2013.01 - EP US)

Cited by  
GB2264400A

Designated contracting state (EPC)  
DE GB

DOCDB simple family (publication)  
**EP 0002984 A1 19790711**; **EP 0002984 B1 19810401**; DE 2860592 D1 19810423; FR 2413807 A1 19790727; FR 2413807 B1 19800822;  
JP S5497795 A 19790802; JP S6138587 B2 19860829; US 4217022 A 19800812

DOCDB simple family (application)  
**EP 78400244 A 19781215**; DE 2860592 T 19781215; FR 7739772 A 19771230; JP 36279 A 19790104; US 97290178 A 19781226