

Title (en)
DEVICE AND METHOD FOR MOULDING SANITARY ARTICLES.

Publication
EP 0002992 B1 19800917 (FR)

Application
EP 78400259 A 19781222

Priority
FR 7739291 A 19771227

Abstract (en)
[origin: EP0002992A2] 1. Device for moulding sanitary articles such as washbasins comprising a mould carried by a frame and provided with a lower half-shell (3), an upper half-shell (4) pivotally mounted on the frame in such a manner as to undergo a pivotal displacement between a closed position in which a mould cavity is defined between the two half-shells and an open position which permits extraction of the moulded article from the lower half-shell (3), and provided with means for the introduction of slip into the mould cavity (5) as well as means of the discharge of slip from the said cavity, characterized in that the mould comprises an intermediate drying flangeplate (8) placed in the closed position between the two half-shells (3, 4) and pivotally coupled to the frame in such a manner as to undergo pivotal displacement between the closed position and at least one position of withdrawal, the said flange-plate (8) being such as to define a peripheral bearing surface on which only the edge of the sanitary article is applied both in the closed position and in the withdrawn position(s) of the said flange-plate.

IPC 1-7
B28B 1/26; B28B 7/00; B28B 17/00

IPC 8 full level
B28B 1/26 (2006.01); **B28B 7/00** (2006.01)

CPC (source: EP)
B28B 1/261 (2013.01); **B28B 7/0044** (2013.01)

Cited by
EP0024160A1; EP0427184A3; US5156855A; WO02053978A1

Designated contracting state (EPC)
BE DE GB IT NL

DOCDB simple family (publication)
EP 0002992 A2 19790711; **EP 0002992 A3 19790725**; **EP 0002992 B1 19800917**; DE 2860184 D1 19801218; ES 476331 A1 19791016; FR 2413190 A1 19790727; FR 2413190 B1 19821217

DOCDB simple family (application)
EP 78400259 A 19781222; DE 2860184 T 19781222; ES 476331 A 19781222; FR 7739291 A 19771227