

Title (en)

System for transforming a two-phase primary flow into several secondary flows.

Title (de)

Vorrichtung zur Umwandlung einer zweiphasigen Primärströmung in mehrere Sekundärströmungen.

Title (fr)

Dispositif pour transformer un écoulement primaire diphasique en plusieurs écoulements diphasiques secondaires.

Publication

EP 0003202 A2 19790725 (FR)

Application

EP 79400026 A 19790112

Priority

FR 7801316 A 19780116

Abstract (en)

1. An apparatus for converting a primary flow of a two-phase fluid into a plurality of secondary flows of two-phase fluid, comprising a tubular body (1), a plurality of radial partitioning walls (3a, 3b, 3c ...) disposed in the tubular body (1) which they divide into as many compartments (10a, 10b, 10c ...) which are separate from each other and whose sections perpendicular to the axis of the tubular body (1) are in the shape of an annular section, said compartments (10a, 10b, 10c ...) opening at the ends of the tubular body (1), and a plurality of outlet conduits (4a, 4b, 4c ...) which are disposed at the same side of one of the ends of the tubular body (1), each of said conduits (4a, 4b, 4c ...) communicating exclusively with one of the compartments (10a, 10b, 10c ...), characterized in that it comprises in combination a hub means (2) which is placed coaxially in the tubular body (1) with which it defines an annular space open at its two ends, said hub means comprising blades (3a, 3b, 3c ...) forming said radial partitioning walls, and flow stabilising means (22) for ensuring rotational symmetry in the distribution of the phases about the axis of the hub means (2) before distribution of the fluid among said outlet conduits (4a, 4b, 4c ...).

Abstract (fr)

Dispositif pour transformer un écoulement primaire de fluide diphasique en plusieurs écoulements secondaires. Il comporte un carter tubulaire, un moyeu placé coaxialement à l'intérieur de ce carter avec lequel il définit un espace annulaire ouvert à ses deux extrémités, une pluralité de pales réparties dans l'espace annulaire qu'elles divisent en autant de compartiments distincts les uns des autres, dont les sections perpendiculaires à l'axe du carter ont une forme de secteur annulaire, ces espaces débouchant aux extrémités du carter, et une pluralité de conduits placés d'un même côté de l'une des extrémités du carter, chacun de ces conduits communiquant exclusivement avec l'un des compartiments. Application à la répartition d'un écoulement de fluide diphasique à grand débit en plusieurs écoulements distincts.

IPC 1-7

F15D 1/14; F16L 41/02

IPC 8 full level

F15D 1/14 (2006.01)

CPC (source: EP)

F15D 1/14 (2013.01)

Citation (applicant)

- DE 800173 C 19501012 - KNORR BREMSE GMBH
- FR 2333139 A1 19770624 - INST FRANCAIS DU PETROLE [FR]

Cited by

AU2012202150B1; EA029748B1; US10465829B2; US7261120B2; WO2013152384A1

Designated contracting state (EPC)

DE GB IT NL

DOCDB simple family (publication)

EP 0003202 A2 19790725; EP 0003202 A3 19790808; EP 0003202 B1 19811028; DE 2961089 D1 19820107; FR 2414651 A1 19790810; FR 2414651 B1 19800516

DOCDB simple family (application)

EP 79400026 A 19790112; DE 2961089 T 19790112; FR 7801316 A 19780116