

Title (en)

Rotary valve.

Title (de)

Drehschieber.

Title (fr)

Tête tournante de robinet.

Publication

EP 0003459 A1 19790808 (FR)

Application

EP 79400046 A 19790124

Priority

- FR 7802123 A 19780126
- FR 7833698 A 19781129

Abstract (en)

1. Rotating tap head (1) designed to be inserted in a tap body (2) and applied to a fluid inlet (4) communicating with the base of this tap body (2), the head comprising at least one annular sealing joint (9) applied to the fluid inlet (4), a lower sealing disc (8) which is fixed and urged towards the sealing joint (9) and which is traversed by at least one fluid flow aperture (12a, 12b) and has a plane polished upper surface (8b) on which may slide, with a rotary movement, and in order to adjust the rate of flow of the fluid traversing this lower disc (8) by complete, partial or non closure of its flow aperture(s) (12a, 12b), inner plane polished surface (7) of an upper sealing disc (7) which is rotationally rigid, by means of supplementary drive projections (15, 16) with a manual rotary control element (6) on the exterior of the tap body (2) and whose lower portion (6a) is, with the sealing discs (7, 8) housed within a substantially cylindrical housing (5, 5a, 5b) having two lateral apertures (14a, 14b) and two longitudinal lugs (17a, 17b, 170a, 170b), this head further comprising two deflectors (13a, 13b) for the lateral deflection towards the lateral apertures (14a, 14b) of the housing (5, 5a, 5b), the fluid arriving from the bottom, and at least one fixed stop engaging with at least one sector which is rotationally rigid with the control element in order to limit the possible angle of rotation of this element, characterized in that the longitudinal lugs (17a, 17b, 170a, 170b) define two spaces between each other constituting the two lateral apertures (14a, 14b) of the housing (5), in that the upper disc (7) has at least one flange (21) constituting an angular limitation sector engaging with a corresponding lateral aperture (14a, 14b) of the housing and which may contact a corresponding longitudinal lug (17a, 17b, 170a, 170b) constituting the said fixed stop, and in that the upper disc (7) has two diametrically opposite recesses (13a, 13b), provided on its periphery, extending from its inner surface and over one portion only of its thickness, and acting in particular as deflectors.

Abstract (fr)

Cette tête de robinet est du type dit "quart de tour" et utilise deux disques d'étanchéité 7,8 susceptibles de tourner l'un par rapport à l'autre sous l'action d'un organe de commande 6 accessible à l'extérieur d'un boîtier 5a, 5b. Le boîtier comprend deux pattes longitudinales 17a, 17b déterminant entre elles des intervalles d'écoulement latéral de fluide. Le disque inférieur est percé et le disque supérieur, qui comporte des oreilles 21 susceptibles de venir en butée contre les pattes 17a, 17b, présente également des cavités faisant office de déflecteurs. L'étanchéité de l'ensemble est de préférence assurée par un joint 9 directement comprimé entre le siège de l'arrivée de fluide et le disque inférieur 8.

IPC 1-7

F16K 3/08

IPC 8 full level

F16K 3/08 (2006.01)

CPC (source: EP)

F16K 3/08 (2013.01)

Citation (search report)

- US 3780758 A 19731225 - DEVRIES R
- FR 2180744 A1 19731130 - AMERICAN STANDARD INC [US]
- US 3698418 A 19721017 - SCHMITT WILLIAM C

Cited by

EP0103710A1; US5107884A; EP0065266A3; US4896693A; US4821765A; DE3145863A1; DE3153188C2; CN108895173A; EP0441335A1; US5732734A; DE3226644A1; DE2944520A1; US5904336A; US5971359A; US6016830A; EP0802361A3; EP0088334A1; DE3045409A1; FR2495266A1; AT385827B; WO9714901A3; WO9201181A1; EP0033428B1; EP0055181B1; EP0035056B1

Designated contracting state (EPC)

BE CH DE GB IT LU NL SE

DOCDB simple family (publication)

EP 0003459 A1 19790808; EP 0003459 B1 19810902; DE 2960712 D1 19811126

DOCDB simple family (application)

EP 79400046 A 19790124; DE 2960712 T 19790124