

Title (en)

METHOD OF MAKING A CRACK-PROOF, IMPERVIOUS JOINT BETWEEN AN ASPHALTIC SURFACING AND PART OF A STRUCTURE, SET OF SHAPED ELEMENTS FOR CARRYING OUT THE METHOD AND STRUCTURE BUILT ACCORDING TO THE METHOD

Publication

**EP 0003720 B1 19820120 (DE)**

Application

**EP 79810013 A 19790205**

Priority

CH 155078 A 19780213

Abstract (en)

[origin: EP0003720A2] 1. Method for crack-proof connection of a layer of asphalt to a building element, particularly to a concrete element, characterized in that, a connecting profile (8) is applied to the building element, which separates the asphalt from the building element when the asphalt layer (3, 16) is applied, and that the connecting profile (8), when the layer of asphalt has at least partially solidified, is spread and elastically compressed, so that the profile is continuously submitted to compressive strains.

IPC 1-7

**E01C 11/02**; **E01D 19/06**

IPC 8 full level

**E01C 11/02** (2006.01); **E01C 11/10** (2006.01); **E01D 19/08** (2006.01); **E02B 3/16** (2006.01); **E04B 1/686** (2006.01); **E04D 13/14** (2006.01)

CPC (source: EP)

**E01C 11/02** (2013.01); **E01C 11/106** (2013.01); **E01D 19/083** (2013.01); **E02B 3/16** (2013.01); **E04D 13/1415** (2013.01)

Cited by

US4875802A; KR20030024015A; EP0385507A1; WO2007048188A1

Designated contracting state (EPC)

DE FR GB NL

DOCDB simple family (publication)

**EP 0003720 A2 19790822**; **EP 0003720 A3 19790905**; **EP 0003720 B1 19820120**; **EP 0003720 B2 19870429**; AT 372442 B 19831010; AT A104979 A 19830215; BE 900408 Q 19841217; CH 628696 A5 19820315; DE 2961845 D1 19820304

DOCDB simple family (application)

**EP 79810013 A 19790205**; AT 104979 A 19790212; BE 213529 A 19840822; CH 155078 A 19780213; DE 2961845 T 19790205