

Title (en)

Device for removing a boot from the foot.

Title (de)

Vorrichtung zum Abziehen eines Stiefels vom Fuss.

Title (fr)

Dispositif tire-bottes.

Publication

**EP 0004297 A1 19791003 (DE)**

Application

**EP 79100606 A 19790301**

Priority

AT 154378 A 19780303

Abstract (en)

[origin: US4243163A] In a boot-jack, the danger of an injuring the uppers of boots is substantially reduced by means of a cladding (4) of elastic material having a Shore hardness of maximum 60 Shore A. The maximum surface pressure exerted is limited by a suitable height dimension of the jaws (6) which are receiving the boot and by a suitable profiling (5) the jaws (6) are well adapted to the outer shape of the boot (FIGS. 1,2).

Abstract (de)

Stiefelknecht, dessen den Stiefel aufnehmender, U-förmiger Fortsatz (3) mit profiliertem elastischem Material (4) einer Härte von maximal 60 shore-A ausgekleidet ist. Die Höhenerstreckung des Fortsatzes (3) entspricht wenigstens dem 2fachen seiner lichten Maulweite.

IPC 1-7

**A47J 51/02**

IPC 8 full level

**A47G 25/80** (2006.01)

CPC (source: EP US)

**A47G 25/80** (2013.01 - EP US)

Citation (search report)

- DE 37393 C
- US 3623640 A 19711130 - ZALEJSKI EDWARD
- DE 66417 C
- US 209091 A 18781015
- GB 1001980 A 19650818 - A E CLEMENTS LTD
- DE 273478 C

Cited by

GB2116830A

Designated contracting state (EPC)

CH DE FR GB IT NL SE

DOCDB simple family (publication)

**EP 0004297 A1 19791003; EP 0004297 B1 19820303;** AU 4456179 A 19790906; DE 2962219 D1 19820401; IT 1114958 B 19860203; IT 7948176 A0 19790301; JP S55174 A 19800105; US 4243163 A 19810106

DOCDB simple family (application)

**EP 79100606 A 19790301;** AU 4456179 A 19790223; DE 2962219 T 19790301; IT 4817679 A 19790301; JP 2260179 A 19790301; US 1634279 A 19790227