

Title (en)  
CODED ELECTRIC SWITCH

Publication  
**EP 0004420 B1 19810826 (EN)**

Application  
**EP 79300326 A 19790306**

Priority  
GB 1058178 A 19780317

Abstract (en)  
[origin: EP0004420A2] An electrical switch comprises a base (1) of electrically insulating material carrying an input contact (3) and a plurality of output contacts (3); a bridging contact (5) fixedly mounted on the base (1) in permanent connection with the input contact (2), and having a plurality of resilient contact arms (6) respectively associated with the output contacts (3), and an operating member mounted on the base and formed with a plurality of cam projections (11) adapted and arranged to engage the contact arms (6) of the bridging contact (5) as the operating member (8) is moved relative to the base (1), thereby to urge the contact arms (6) into contact with the associated output contacts (3).

IPC 1-7  
**H01H 19/63**

IPC 8 full level  
**H01H 19/63** (2006.01)

CPC (source: EP)  
**H01H 19/63** (2013.01)

Cited by  
EP0036263B1

Designated contracting state (EPC)  
BE CH DE FR GB IT NL SE

DOCDB simple family (publication)  
**EP 0004420 A2 19791003; EP 0004420 A3 19791031; EP 0004420 B1 19810826;** AR 215378 A1 19790928; AT 374962 B 19840625; AT A195279 A 19831015; AU 4459579 A 19790920; AU 517410 B2 19810730; BR 7901664 A 19791016; DE 2960674 D1 19811119; DK 109679 A 19790918; DK 145478 B 19821122; DK 145478 C 19830418; ES 478645 A1 19791101; FI 790785 A 19790918; JP S54129491 A 19791006; MX 144630 A 19811030; NO 147576 B 19830124; NO 147576 C 19830504; NO 790663 L 19790918

DOCDB simple family (application)  
**EP 79300326 A 19790306;** AR 27580379 A 19790314; AT 195279 A 19790315; AU 4459579 A 19790226; BR 7901664 A 19790316; DE 2960674 T 19790306; DK 109679 A 19790316; ES 478645 A 19790315; FI 790785 A 19790307; JP 3054179 A 19790315; MX 17696179 A 19790316; NO 790663 A 19790227