

Title (en)

AN APPARATUS FOR LINE-TO-LINE RECORDING OF DIFFERENT COLOR COMPONENT IMAGES

Publication

**EP 0004736 B1 19811104 (EN)**

Application

**EP 79300480 A 19790326**

Priority

- US 89280978 A 19780403
- US 89281078 A 19780403

Abstract (en)

[origin: EP0004736A2] An apparatus for line-to-line recording of different color component images. Four separate xerographic type processing units (111, 112, 113, 114), one for each of the primary colors plus black, are arranged in close nested relationship to one another with image transfer stations (68, 69, 70, 71) in close succession along the path of movement of the copy sheets (12). A combination air flotation type (35) and vacuum based belt transport system (55) is used to move the copy sheets (12) from supply tray (27) successively past the processing units. Exposure is simultaneous. A precise dimensional relationship between the length (L) and spacing (D) of each photoreceptor belt (110) assures registration of the color images with one another. The length of each photoreceptor belt (110) is the same. Vacuum tensioning means (122) provides the preset dimensional relationship (L, D) between each photoreceptor belt (110). Plural flying spot beams (261 min , 262 min , 263 min , 264 min ) derived from laser (222) provide simultaneous exposure of each photoreceptor belt.

IPC 1-7

**G03G 15/01**

IPC 8 full level

**G03G 15/01** (2006.01)

CPC (source: EP)

**G03G 15/0194** (2013.01); **G03G 2215/00586** (2013.01)

Cited by

EP0547853A3; US5215891A; GB2192152A; GB2263086A; US5379056A; US5448281A; GB2263086B

Designated contracting state (EPC)

DE FR GB NL

DOCDB simple family (publication)

**EP 0004736 A2 19791017; EP 0004736 A3 19791031; EP 0004736 B1 19811104**; DE 2961203 D1 19820114; JP S54134439 A 19791018

DOCDB simple family (application)

**EP 79300480 A 19790326**; DE 2961203 T 19790326; JP 3618079 A 19790327