

Title (en)

INDUSTRIAL SCREEN FOR PREPARATION OF LOOSE MATERIAL.

Title (de)

INDUSTRIE-SIEBBODEN ZUR AUFBEREITUNG VON SCHÜTTGÜTERN.

Title (fr)

CRIBLE INDUSTRIEL POUR LA PREPARATION DE MATERIAUX EN VRAC.

Publication

EP 0007380 A1 19800206 (DE)

Application

EP 78900313 A 19790621

Priority

DE 2754044 A 19771205

Abstract (en)

[origin: DE2754044B1] The industrial screen is essentially composed of a support frame (1) and of several sieves (2 and 3) which can be fixed by means of different slats (4, 5 and 6) to the support frame (1). The slats are fixed to the support frame (1) by bolts. The frontal slat (4) fixed to the support frame (1) is made up of an angle-bar which covers one edge of the sieve of side (2). Opposite to the front side, the said sieves (2) and the adjoining sieves (3) are provided with grooves which extend perpendicularly to the length of the screen. Into these longitudinal grooves fits a tightening slat (5) which can be fixed to the support frame (1). Other sieves (2) provided with an edge are added to the central sieves (3). The central sieves (3), and the outer sieves (2) are also fixed by means of a tightening slat (5). The outer sieves (2) are also fixed with other identical sieves (2) to the support frame (1) by means of an assembly slat (6) which has a T section and hence covers the edges of said sieves (2). The use of assembly (6), tightening (5) and frontal (4) slats allows to assemble and disassemble all the sieves (2 and 3) from the top of the industrial screen. Also, it is easy to replace worn out sieves.

Abstract (fr)

Le crible industriel se compose essentiellement d'un cadre de soutien (1) ainsi que de plusieurs tamis (2 et 3) qui peuvent étre fixés au moyen de différentes listes (4, 5 et 6) au cadre de soutien (1). Les listes sont fixées au cadre de soutien (1) par des boulons. La liste (4) fixée frontalement au cadre de soutien (1) est constituée d'une cornière qui recouvre un rebord du tamis de bord (2). Du côté opposé au côté frontal lesdits tamis (2) et les tamis voisins (3) sont munis de rainures qui courrent perpendiculairement à la longueur du crible. Dans ces rainures longitudinales s'insère une liste de serrage (5) qui peut étre fixée au cadre de soutien (1). D'autres tamis (2) munis de rebords s'ajoutent aux tamis centraux (3). Les tamis centraux (3), et les tamis extérieurs (2) sont aussi fixes à l'aide d'une liste de serrage (5). Les tamis extérieurs (2) sont fixes avec d'autres tamis (2) identiques, au cadre de soutien (1) au moyen d'une liste de montage (6), qui a une section en T et qui par conséquent couvre les rebords desdits tamis (2). L'utilisation des listes de montage (6), de serrage (5) et de bord (4) permet de monter ou de démonter tous les tamis (2 et 3) depuis le dessus du crible industriel. De même, il est facile de changer les tamis usages.

IPC 1-7

B07B 1/46

IPC 8 full level

B07B 1/46 (2006.01)

CPC (source: EP)

B07B 1/4645 (2013.01); **B07B 1/469** (2013.01)

Cited by

EP2070903A1

Designated contracting state (EPC)

CH FR GB LU SE

DOCDB simple family (publication)

DE 2754044 B1 19790419; EP 0007380 A1 19800206; WO 7900341 A1 19790614

DOCDB simple family (application)

DE 2754044 A 19771205; DE 7800036 W 19781202; EP 78900313 A 19790621