

Title (en)  
Indoor lighting fixture.

Title (de)  
Innenleuchte.

Title (fr)  
Appareil d'éclairage intérieur.

Publication  
**EP 0008006 A1 19800220 (DE)**

Application  
**EP 79102357 A 19790709**

Priority  
• DE 2834285 A 19780804  
• DE 2923591 A 19790611

Abstract (en)  
1. An interior light-fitting comprising a symmetrical, wide-angle channel reflector for, a fluorescent lamp arranged in the plane of symmetry of the channel reflector, comprising two parabolic side reflectors whose respective main radiation paths cross the plane of symmetry, two top reflectors whose respective main radiation paths each lie on that side of the plane of symmetry that the respective top reflector lies, the outer edges of the top reflectors and the upper edges of the side reflectors lie above the lower horizontal plane of tangency to the fluorescent lamp, characterized in that the main axis (H1, H1') of each side reflector (1, 1') forms an angle  $\beta$  with the vertical (E) having a value of between 30 degrees and 45 degrees, in particular of 40 degrees, the focal length of the side reflectors (1, 1') being given by the quotient of half the diameter (D) of the fluorescent lamp (3) and the sine of the scattering angle ( $\alpha$ ), which lies between 7 degrees and 18 degrees, the top reflectors (2, 2') each having the shape of a parabola whose main axis forms an angle with respect to the vertical (E) having a value of between 25 degrees and 45 degrees, in particular of 30 degrees, the outer edge (21, 21') of each top reflector (2, 2') lying on a path from the centre of the fluorescent lamp (3) to a respective upper edge (11, 11') of the adjacent side reflector, by which it is reflected past the lamp, the focal length (S2, S2') of the parabola of the top reflectors (2, 2') being selected such that at least 80 % of the beams from the centre of the fluorescent lamp (3) and are reflected past the lamp by a side reflector (2, 2') emerge from the interior light-fitting without further reflection, and the focal points (F1, F2) of the parabolas of the top and side reflectors (1, 1' ; 2, 2') all coinciding at the centre (M) of the fluorescent lamp (3).

Abstract (de)  
Es sind Rinnenspiegel für Leuchtstofflampen bekannt, die eine breitstrahlende Lichtverteilung mit einem ausgeprägten Minimum um 0° haben. Letzteres wird durch Abschirmung der Lampe oder durch Prismenscheiben erreicht, worunter jedoch der Wirkungsgrad der Leuchte leidet. Der Erfindung liegt die Aufgabe zugrunde, den Wirkungsgrad und das Verhältnis von maximaler Lichtstärke zu minimaler zu verbessern, wobei die maximale Lichtstärke unter einem möglichst hohen Winkel auftreten soll, ohne daß darunter die Qualität der Abschirmung leidet. Dies wird gemäß der Erfindung im wesentlichen durch zwei unter hohem Winkel über Kreuz strahlenden, parabolischen Seitenspiegeln (1, 1') in Verbindung mit zwei nicht über Kreuz strahlenden, abolischen Dachspiegeln (2, 2') erreicht, wobei die Brennpunkte im Mittelpunkt der Lampe liegen und die Abmessungen so groß gewählt sind, daß sich ein möglichst kleiner Streuwinkel ergibt.

IPC 1-7  
**F21V 7/06**; G02B 5/10

IPC 8 full level  
**F21V 7/06** (2006.01)

CPC (source: EP)  
**F21V 7/06** (2013.01)

Citation (search report)  
• GB 516012 A 19391220 - BRITISH THOMSON HOUSTON CO LTD, et al  
• DE 217742 C

Cited by  
US4747027A; FR2566819A1; EP0442246A3; AU679737B2; AU679737C

Designated contracting state (EPC)  
AT CH IT SE

DOCDB simple family (publication)  
**EP 0008006 A1 19800220**; **EP 0008006 B1 19820203**; GR 72391 B 19831101

DOCDB simple family (application)  
**EP 79102357 A 19790709**; GR 790159759 A 19790802