

Title (en)
FASTENER-DRIVING APPARATUS

Publication
EP 0008749 B1 19810902 (DE)

Application
EP 79103098 A 19790823

Priority
DE 2838194 A 19780901

Abstract (en)
[origin: ES483777A1] The present driver for fasteners such as nails, screws and the like is provided with a separator member operatively located between the ejector channel and a fastener supply magazine. The separator member takes up a fastener arresting position in which the separator member reaches between the shafts of two fasteners and a retracted position in which the separator member releases a fastener for movement into the ejector channel. The separator member cooperates with a holding device which holds a fastener in the ejector channel after release by the separator member and prior to the driving stroke. The holding device may comprise two permanent magnets.

IPC 1-7
B25C 1/04

IPC 8 full level
B27F 7/09 (2006.01); **B25C 1/00** (2006.01); **B25C 1/04** (2006.01)

CPC (source: EP US)
B25C 1/005 (2013.01 - EP US)

Cited by
EP0738564A1; US5839332A; GB2225974A; GB2225974B; EP0644020A3; US5683024A; EP0174160A1; US4598852A; EP0044985B1; EP0057179B1

Designated contracting state (EPC)
AT BE CH FR GB IT NL SE

DOCDB simple family (publication)
EP 0008749 A1 19800319; EP 0008749 B1 19810902; AT E176 T1 19810915; BR 7905483 A 19800513; CA 1112115 A 19811110; DE 2838194 A1 19800313; DE 2838194 B2 19810709; DE 2838194 C3 19820211; ES 483777 A1 19800701; JP H0228009 Y2 19900727; JP S5534992 A 19800311; JP S60166508 U 19851105; US 4270687 A 19810602

DOCDB simple family (application)
EP 79103098 A 19790823; AT 79103098 T 19790823; BR 7905483 A 19790827; CA 333926 A 19790816; DE 2838194 A 19780901; ES 483777 A 19790831; JP 10976679 A 19790830; JP 2979785 U 19850304; US 6874679 A 19790823