

Title (en)

CIRCUIT BREAKER WITH SEPARATED MAIN AND SHUNT CURRENT PATHS

Publication

EP 0011542 B1 19830720 (FR)

Application

EP 79400819 A 19791105

Priority

FR 7832214 A 19781114

Abstract (en)

[origin: US4309581A] A puffer-type gas-blast circuit-breaker comprises an interrupting unit mounted in a housing filled with an insulating gas of high dielectric strength such as sulfur hexafluoride. The interrupting unit includes a main circuit having a pair of stationary and movable main contacts, and an arcing circuit having a pair of stationary and movable arcing contacts. An operating mechanism comprises a control rod coupled to the movable contacts so as to open the main contacts before the separation of the arcing contacts. A pair of input and output terminals extend out of the housing, and a shunt conductor is arranged in the arcing circuit between operating rod and the lower terminal. The longitudinally extending main and arcing circuits are connected in parallel to the terminals and form two independent current paths which are cross-wise spaced inside the housing. A partition wall divides the inner space of the housing into two superposed compartments, one of them including the main contacts, and the other the arcing zone.

IPC 1-7

H01H 33/12; H01H 33/91

IPC 8 full level

H01H 33/88 (2006.01); **H01H 33/00** (2006.01); **H01H 33/12** (2006.01); **H01H 33/91** (2006.01); **H01H 33/915** (2006.01)

CPC (source: EP US)

H01H 33/122 (2013.01 - EP US); **H01H 33/91** (2013.01 - EP US)

Cited by

FR2631735A1; EP0194489A3; EP0240406A1; FR2596915A1; EP0398213A1; FR2647254A1; US4996398A; EP0749139A1; FR2735277A1; CN1068963C; EP0239460A1; FR2596576A1; US4748304A; EP0450567A1; FR2660792A1; US5155314A; EP0517620A1; FR2677168A1; US5239150A; EP0378950A1; FR2641898A1; US5095183A

Designated contracting state (EPC)

BE CH DE GB IT NL SE

DOCDB simple family (publication)

EP 0011542 A1 19800528; EP 0011542 B1 19830720; EP 0011542 B2 19880210; CS 231167 B2 19841015; CS 761579 A2 19840213; DE 2965950 D1 19830825; FR 2441916 A1 19800613; FR 2441916 B1 19811002; JP H0139171 B2 19890818; JP S5568021 A 19800522; US 4309581 A 19820105

DOCDB simple family (application)

EP 79400819 A 19791105; CS 761579 A 19791108; DE 2965950 T 19791105; FR 7832214 A 19781114; JP 14635279 A 19791112; US 8739479 A 19791022