

Title (en)  
APPARATUS FOR ELECTRODEPOSITION OF ALUMINIUM

Publication  
**EP 0013874 A3 19810107 (DE)**

Application  
**EP 80100008 A 19800103**

Priority  
DE 2901586 A 19790117

Abstract (en)  
[origin: US4265726A] To prevent transport of deleterious oxygen and moisture to liquid electrolyte in an aluminum electroplating vessel, workpieces move towards the vessel through an antechamber containing inert gas under pressure and comprising a plenum chamber opening downwardly into a lock chamber containing aprotic liquid. They move down into the liquid, then up out of it, into and through an inverted-U-shaped passageway containing higher pressure inert gas and which communicates with the lock chamber below the surface of the liquid therein and communicates with the electrolysis vessel above the surface of the electrolyte. At each connection between parts, where atmospheric oxygen might move towards the electrolyte, there are double mechanical seals defining a substantially annular chamber filled with aprotic liquid that forms a gas barrier, and such liquid is, where possible, shielded by inert gas.

IPC 1-7  
**C25D 17/00**

IPC 8 full level  
**C25D 17/00** (2006.01); **C25D 21/11** (2006.01)

CPC (source: EP US)  
**C25D 5/003** (2013.01 - EP US); **C25D 17/004** (2013.01 - EP US)

Citation (search report)

- DE 2716805 A1 19781026 - SIEMENS AG
- DE 2719641 A1 19781109 - MONTBLANC SIMPLO GMBH
- DE 2443361 A1 19760429 - MONTBLANC SIMPLO GMBH
- DE 2537256 A1 19770224 - SIEMENS AG
- DE 2719680 A1 19781109 - MONTBLANC SIMPLO GMBH

Cited by  
CN1037630C; US4668367A; EP0056844A1; US4759831A; DE3044975A1; EP0053676A1; EP0060929A1

Designated contracting state (EPC)  
AT CH FR GB NL

DOCDB simple family (publication)  
**EP 0013874 A2 19800806; EP 0013874 A3 19810107; EP 0013874 B1 19840314**; AT E6677 T1 19840315; DE 2901586 A1 19800731; JP S55115994 A 19800906; JP S6332880 B2 19880701; US 4265726 A 19810505

DOCDB simple family (application)  
**EP 80100008 A 19800103**; AT 80100008 T 19800103; DE 2901586 A 19790117; JP 315580 A 19800117; US 11010680 A 19800107