

Title (en)
PROCESS FOR PRINTING VOLUMINOUS TEXTILES

Publication
EP 0014890 A3 19810107 (DE)

Application
EP 80100558 A 19800204

Priority
DE 2904223 A 19790205

Abstract (en)
[origin: EP0014890A2] In the process, the lofty textile materials are first prepared with a) a synthetic thickener, b) a bath which contains a synthetic thickener and a dye, or c) an electrolyte-containing padding liquor or an electrolyte-containing print paste, and then, in the case of measures a) and b), printed with an electrolyte-containing print paste and in the case of measure c) printed with a print paste which has been thickened with a synthetic thickener. This produces fully penetrating prints having crisp contours.

IPC 1-7
D06P 5/00; **D06P 3/06**; **D06P 1/52**

IPC 8 full level
D06P 1/52 (2006.01); **D06P 3/06** (2006.01); **D06P 5/00** (2006.01)

CPC (source: EP)
D06P 1/525 (2013.01); **D06P 3/06** (2013.01); **D06P 5/001** (2013.01)

Citation (search report)

- GB 2012313 A 19790725 - SANDOZ LTD
- DE 2304104 A1 19740110 - ZIMMER JOHANNES
- DE 2410155 A1 19750911 - BASF AG
- DE 2641159 A1 19770331 - SANDOZ AG
- CH 757873 A
- MELLIAND TEXTILBERICHTE, Band 49, Nr. 11, November 1968, Seiten 1331-1336 Heidelberg, DE. "Teil II: Praxiserfahrungen mit vollsynthetischen Verdickungsmitteln" * Seite 1331, rechte Spalte, 2. Halfte *

Cited by
EP0054191A3; EP1072719A1; US6673394B1

Designated contracting state (EPC)
AT CH DE FR GB IT NL

DOCDB simple family (publication)
EP 0014890 A2 19800903; **EP 0014890 A3 19810107**; DE 2904223 A1 19800814; ES 488251 A1 19800916

DOCDB simple family (application)
EP 80100558 A 19800204; DE 2904223 A 19790205; ES 488251 A 19800204