

Title (en)

DEVICE FOR SECURING A NEEDLE STRIP IN A U-SECTION HOLDER OF TEXTILE MACHINES WITH PINNED BARS

Publication

**EP 0015360 B1 19811223 (DE)**

Application

**EP 80100124 A 19800111**

Priority

DE 2909525 A 19790310

Abstract (en)

[origin: US4266327A] A releasably interlockable needlestrip and needle-carrier for textile machines includes a generally U-shaped elongated needle carrier having legs defining a longitudinally extending recess therebetween. A plurality of protuberances are provided on one of the legs projecting into the recess. A bracket member is positionable in abutting relationship with a needlestrip and one of the legs thereof is positionable in abutting relationship with the top face of the needlestrip, the needlestrip and bracket member when positioned in such abutting relationship being dimensioned and configured to fit within the recess of the needle carrier. A plurality of slots are formed in the surface of one leg of the bracket member with each slot having a first vertically extending segment and a second longitudinally extending segment, the protuberances and slots being so configured and arranged on the needle-carrier and bracket member that upon insertion of the needlestrip and bracket member into the recess of the needle-carrier, the protuberances are alignable with the segments of corresponding slots and are slidable therein for mechanical and releasable interlocking of the needlestrip, bracket member and needle-carrier.

IPC 1-7

**D01H 5/14**

IPC 8 full level

**D01H 5/14** (2006.01)

CPC (source: EP US)

**D01H 5/14** (2013.01 - EP US)

Cited by

CN111139534A; GB2182364A

Designated contracting state (EPC)

AT BE CH FR GB IT LU NL SE

DOCDB simple family (publication)

**EP 0015360 A1 19800917; EP 0015360 B1 19811223**; AT E491 T1 19820115; CS 208799 B2 19810915; DD 149387 A5 19810708; DE 2909525 A1 19800911; DE 2909525 C2 19820616; US 4266327 A 19810512

DOCDB simple family (application)

**EP 80100124 A 19800111**; AT 80100124 T 19800111; CS 164080 A 19800310; DD 21946780 A 19800305; DE 2909525 A 19790310; US 11961180 A 19800208