

Title (en)
Gas blast circuit breaker.

Title (de)
Elektrischer Druckgasschalter.

Title (fr)
Disjoncteur à gaz comprimé.

Publication
EP 0015865 A1 19800917 (DE)

Application
EP 80730011 A 19800215

Priority
DE 2908982 A 19790306

Abstract (en)
[origin: US4354073A] An electric gas blast circuit breaker is disclosed which has two stationary contact pieces. A switching unit is movable between closed and open positions for electrically bridging the contact pieces in the closed position and for electrically disconnecting the contact pieces in the open position whereby an arc develops when the switching unit is moved to the open position. A gas blast device blasts a stream of gas through the arc when the switching unit is moved to the open position. The switching unit includes a supporting body and a slide-contact ring made of an arc-resistant material. The ring slideably contacts one of the contact pieces in the closed position and is mounted on the supporting body so as to be electrically insulated therefrom. A plurality of elongated contact elements are disposed in the supporting body for electrically connecting the contact pieces when the switching unit is in the closed position. There is provided an electrical connection between at least one of the contact elements and the slide-contact ring when the switching unit is in the closed position and also when it moves into the open position and continuously in all operating positions thereof.

Abstract (de)
Bei einem elektrischen Druckgasschalter mit einer aus Kolben und Zylinder bestehenden Blaseinrichtung sind zwei feststehende düsenförmige Schaltstücke (2, 3) vorgesehen, die in der Einschaltstellung durch ein rohrförmiges Überbrückungsschaltstück (6) miteinander verbunden sind. Das Überbrückungsschaltstück (6) besteht aus im Innern einer rohrförmigen Hülse (6a) federnd gelagerten Kontaktlamellen (7) und einem stirnseitig unter Zwischenlage einer elektrischen Isolierung gefaßten Gleitkontaktring (8) aus lichtbogenbeständigem Material. Um eine unverzögerte Kommutierung des Stromes während des Ausschaltvorganges von den Kontaktlamellen (7) auf den Gleitkontaktring (8) zu bewirken, ist zumindest eine der Kontaktlamellen (7) ständig mit dem Gleitkontaktring (8) elektrisch leitend verbunden. Hierfür kann die Kontaktlamelle (7) federnd gegen den Gleitkontaktring (8) gedrückt sein oder über ein flexibles Stromband elektrisch verbunden sein.

IPC 1-7
H01H 33/91

IPC 8 full level
H01H 33/88 (2006.01); **H01H 33/91** (2006.01); **H01H 33/915** (2006.01)

CPC (source: EP US)
H01H 33/91 (2013.01 - EP US)

Citation (search report)
• FR 2177804 A2 19731109 - SIEMENS AG [DE]
• FR 2181860 A2 19731207 - SIEMENS AG [DE]

Cited by
EP0665565A3

Designated contracting state (EPC)
AT BE CH FR GB IT LU NL SE

DOCDB simple family (publication)
EP 0015865 A1 19800917; **EP 0015865 B1 19820120**; AT E600 T1 19820215; BR 8001302 A 19801104; CA 1148593 A 19830621; DE 2908982 A1 19800918; DE 2908982 B2 19810507; DE 2908982 C3 19820128; JP S55127348 U 19800909; JP S6031142 Y2 19850918; MX 147086 A 19820930; US 4354073 A 19821012; ZA 801275 B 19810325

DOCDB simple family (application)
EP 80730011 A 19800215; AT 80730011 T 19800215; BR 8001302 A 19800305; CA 347012 A 19800305; DE 2908982 A 19790306; JP 2939880 U 19800306; MX 18142380 A 19800304; US 12620680 A 19800303; ZA 801275 A 19800305