

Title (en)

METHOD AND DEVICE FOR SUPPLYING LUBRICANT TO A PISTON AND CYLINDER ARRANGEMENT

Publication

EP 0017100 B1 19850306 (DE)

Application

EP 80101491 A 19800321

Priority

CH 326279 A 19790406

Abstract (en)

[origin: US4384510A] The method and the device for the lubricant feed works by introduction of the lubricant into a clearance volume (3b) between a, for example, tubular flexible sealing element of a cylinder-piston arrangement and a bearing surface within the working stroke at comparatively low working pressure. Consequently a comparatively low lubricant feed pressure is adequate. Return of lubricant into the feed is advantageously excluded by a non-return valve arrangement (8d,15). Preferably a non-return valve member (15) is arranged in the region of the mouth (9) from the lubricant feed, whereby low-inertia operation results with secure maintenance of pressure in the lubricant space (3b).

IPC 1-7

F01M 1/16; F04B 43/08

IPC 8 full level

F04B 53/18 (2006.01); **F01M 1/16** (2006.01); **F04B 43/08** (2006.01); **F16N 7/36** (2006.01)

CPC (source: EP US)

F01M 1/16 (2013.01 - EP US); **F04B 43/084** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LU NL SE

DOCDB simple family (publication)

EP 0017100 A2 19801015; EP 0017100 A3 19810107; EP 0017100 B1 19850306; AR 223868 A1 19810930; AT E12044 T1 19850315;
AU 540832 B2 19841206; AU 5717180 A 19801009; BR 8002065 A 19801125; CH 642145 A5 19840330; CS 258459 B2 19880816;
DD 150102 A5 19810812; DE 3070250 D1 19850411; HU 182116 B 19831228; JP S55139594 A 19801031; JP S6365829 B2 19881216;
MX 153130 A 19860808; PL 130978 B1 19840929; PL 223294 A1 19810116; US 4384510 A 19830524; ZA 801966 B 19810429

DOCDB simple family (application)

EP 80101491 A 19800321; AR 28051380 A 19800331; AT 80101491 T 19800321; AU 5717180 A 19800403; BR 8002065 A 19800402;
CH 326279 A 19790406; CS 235780 A 19800404; DD 22021480 A 19800403; DE 3070250 T 19800321; HU 79080 A 19800402;
JP 4511280 A 19800405; MX 18179880 A 19800331; PL 22329480 A 19800405; US 13650080 A 19800403; ZA 801966 A 19800402