

Title (en)

Electronically controlled printing mechanism.

Title (de)

Elektronisch gesteuertes Schreibwerk.

Title (fr)

Mécanisme d'impression à commande électronique.

Publication

EP 0018311 A1 19801029 (DE)

Application

EP 80730028 A 19800327

Priority

DE 2915720 A 19790414

Abstract (en)

1. Electronically controlled printing mechanism of modular design for either manually or mechanically fed papers, characterized by the following components : a) a basic module consisting of a desk (3), two friction rollers (6) for feeding the paper, a toothed belt (7) which drives them and which is driven by a large wheel (8) via a pinion (9) by means of an electric motor (10), counter rollers (12) for pressing the paper against the two friction rollers (6), a light barrier (14) arranged at one end of the paper track (4) for generating a pulse to start the feeding of the paper when the paper is fed manually from this end, and a second light barrier (15) for generating pulses for the print and control timing which are triggered when the toothed wheel rim of the large wheel (8) passes through the light barrier (15) so that one pulse per column of a needle character and/or per bit of the magnetic type can be picked up at the toothed wheel rim of the gear wheel (8) for the paper transport, and that the number of teeth on the large wheel (8) is selected such that one tooth corresponds to one column of a needle character or to one bit of the magnetic type, respectively ; b) a supplementary module to enable conversion from the longitudinal type to the transverse type process, consisting of a threaded spindle (16) mounted vertically in relation to the paper feeding device for moving a carriage carrying the printing heads (1 and 13, respectively) along the spindle, a rod (17) for guiding this carriage, a large wheel (18) which drives the threaded spindle (16) via a pinion (19) and via an electric motor (20), and a light barrier (21) for generating pulses for the print and control timing which is effected by means of pulses which are triggered when the toothed wheel rim of the large wheel (18) passes through the light barrier (21), with the number of teeth on the large wheel (18) in combination with the pitch of the threaded spindle (16) being selected such that, as in the case of the basic module according to a), one tooth corresponds to one column of a needle character or to one bit of the magnetic type, respectively ; c) a supplementary module consisting of a printing head (13) mounted on the desk (3) for machine-readable type and/or an electronically controlled printing head (1) arranged above the desk (3) for visually-readable type with a ribbon cartridge (2) and a motor, with the printing head (1) for visually-readable type being swivable through 90 degrees at the carriage for conversion from the longitudinal type to the transverse type process, and the control leads for the motors (10, 20) and the light barriers (15, 21) being exchangeable to enable use of the same print program ; d) a supplementary module for mechanical paper feed from the other end of the paper track (4) opposite the light barrier (14), consisting of a third friction roller (6), a wedge member (11) serving as one longitudinal side of the paper feed channel (5), a rocker (22) mounted longitudinally along the other side of the channel, with a brake shoe (26) pressable against the wedge member (11) to clamp the paper, and with a counter roller (23), with the rocker (22), when caused to swivel by an actuating magnet (24), pressing the counter roller (23) against the friction roller (6) to activate the paper feed from this end of the paper track and moving the brake shoe (26) away from the wedge member (11) so that the paper is freely movable through the feeding channel (5), and a pulse-controlled cutting device (30-35) provided at the opposite end of the paper track (4) adjacent to the light barrier (14) ; e) a supplementary module located adjacent to the supplementary module according to d) for generating pulses for proper form synchronization, consisting of a light rod (27) and a phototransistor (28) which scans form sheets provided with control apertures and provides corresponding synchronization pulses.

Abstract (de)

Die Erfindung betrifft ein elektronisch gesteuertes Schreibwerk in modularer Bauweise für wahlweise manuell oder maschinell zugeführte Papiere. Es ist aufgebaut aus einem Grundmodul, bestehend aus einem Schreibtisch (3) mit zwei Frikionswalzen (6), einem Zahnrämen (7), einem Großrad (8), einem Ritzel (9), einem Elektromotor (10), Gegenrollen (12) und Lichtschranken (15). Hinzugefügt werden können ein oder mehrere Ergänzungsmodulen, von denen das eine aus einer am Schreibtisch angeordneten Schreibeinrichtung (13) für maschinell lesbare Schrift und/oder einer über dem Schreibtisch angeordneten schwenkbaren elektronisch gesteuerten Schreibeinrichtung für visuell lesbare Schrift mit Farbbandkassette (2) und mit Motor besteht; ein weiteres Ergänzungsmodul besteht aus einer Gewindespindel (16), einer Stange (17) einem Großrad (18), einem Ritzel (19), einem Elektromotor (20) und einer Lichtschranke (2); ein weiteres Ergänzungsmodul besteht aus einer dritten Frikionswalze (6), einem Teilstück (11), einer Wippe (22), einer Gegenrolle (23), einem Betätigungsmaßstab (24), einem Bremsklötz (26) und einer taktgesteuerten Schneideeinrichtung (30) und ein weiteres Ergänzungsmodul besteht aus einem Lichtstab (27) und einem Fototransistor (28). Die beiden Schreibeinrichtungen können gleichzeitig oder abwechselnd arbeiten.

IPC 1-7

B41J 29/02; G07B 1/00

IPC 8 full level

B41J 29/02 (2006.01); B41J 29/38 (2006.01); G07B 1/00 (2006.01)

CPC (source: EP)

B41J 29/02 (2013.01); G07B 1/00 (2013.01)

Citation (search report)

- FR 2385533 A1 19781027 - LRC INC [US]
- DE 2807405 A1 19790823 - MANNESMANN AG
- FR 2347200 A1 19771104 - SIEMENS AG [DE]
- DE 2607391 A1 19770825 - ANKER WERKE AG
- DE 2716396 A1 19781019 - SIEMENS AG
- DE 2150343 A1 19720413 - CARRUS ANDRE, et al
- FR 2334501 A1 19770708 - DASSAULT ELECTRONIQUE [FR]

Cited by

CN112008793A

Designated contracting state (EPC)

AT CH DE FR IT NL SE

DOCDB simple family (publication)

EP 0018311 A1 19801029; EP 0018311 B1 19840208; AT E6139 T1 19840215; DE 2915720 A1 19801016; DE 3066459 D1 19840315;
DK 156080 A 19801015

DOCDB simple family (application)

EP 80730028 A 19800327; AT 80730028 T 19800327; DE 2915720 A 19790414; DE 3066459 T 19800327; DK 156080 A 19800411