

Title (en)

LASER BEAM SIGHTING AID FOR HAND FIREARMS

Publication

EP 0018769 B1 19850102 (EN)

Application

EP 80301303 A 19800423

Priority

- US 3328479 A 19790425
- US 3328579 A 19790425

Abstract (en)

[origin: EP0018769A2] In order to prevent thermal effects, stresses and other operating conditions from affecting the operation of the laser (15), the tubular member (25) holding the laser (15) is mounted on the firearm (12) at a first location (27) and is there provided with linear freedom of movement relative to the firearm (12), and is further mounted on the firearm (12) at a second location (28), where it provides the tubular member (25) with angular freedom of movement relative to the firearm (12). For actuating the laser (15) with certainty before the firing pin, either, a lost-motion connection between trigger (91) and hammer (87) is provided, in the course of which the switch (83) for energizing the laser (15) is being closed, or, the switch (83) is being closed by manually cocking the hammer (87), the latter being released from that position by actuating the trigger (91).

IPC 1-7

F41G 1/34

IPC 8 full level

F41G 1/34 (2006.01); **F41G 1/387** (2006.01); **F41G 11/00** (2006.01)

CPC (source: EP)

F41G 1/34 (2013.01); **F41G 11/001** (2013.01)

Cited by

EP1596152A1; DE102004023556B4; US7644530B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0018769 A2 19801112; EP 0018769 A3 19810603; EP 0018769 B1 19850102; DE 3069894 D1 19850214

DOCDB simple family (application)

EP 80301303 A 19800423; DE 3069894 T 19800423