

Title (en)
CONNECTING DEVICE FOR INSULATED ELECTRICAL CONDUCTORS

Publication
EP 0020241 B1 19840404 (FR)

Application
EP 80400708 A 19800521

Priority
FR 7913326 A 19790525

Abstract (en)
[origin: WO8002775A1] Connection device of isolated electric conductors by a self-stripping connector comprising a conductive connecting part of the fork or pincer type having at least two resilient branches providing therebetween a slot wherein the electric conductor to be connected is inserted, the connecting part being intended to be introduced into a cavity of a socket of insulating material. The double fork type connecting part (75) comprises two inclined slots (64, 65) of which the axes convert towards the top of the connector. Application: electric connection, particularly in telecommunications.

IPC 1-7
H01R 4/24

IPC 8 full level
H01R 4/24 (2006.01)

CPC (source: EP US)
H01R 4/2425 (2013.01 - EP US)

Cited by
EP0237141A3; FR2664433A1; FR2580430A1; TR24783A; US4451867A; EP0321726A3; WO9108599A1

Designated contracting state (EPC)
AT BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0020241 A1 19801210; EP 0020241 B1 19840404; AT E6970 T1 19840415; CA 1145429 A 19830426; DE 3067324 D1 19840510; FR 2457574 A1 19801219; FR 2457574 B1 19821203; JP S56500591 A 19810430; JP S6335072 B2 19880713; US 4350405 A 19820921; WO 8002775 A1 19801211

DOCDB simple family (application)
EP 80400708 A 19800521; AT 80400708 T 19800521; CA 352591 A 19800523; DE 3067324 T 19800521; FR 7913326 A 19790525; FR 8000084 W 19800521; JP 50115480 A 19800521; US 23204481 A 19810125