

Title (en)
COOLING DEVICE FOR HOT ROLLED ELONGATE LAMINATED PRODUCTS

Publication
EP 0020246 B1 19850213 (FR)

Application
EP 80400715 A 19800521

Priority
FR 7914383 A 19790601

Abstract (en)
[origin: EP0020246A1] 1. A cooling device for continuously rolled elongated products, comprising a water injection head (11) located between two aligned cooling tubes (2, 4) through which pass a thin layer of water, with the product continuously travelling between said tubes, device according to which said injection head (1) obtaining a watertight connection between said tubes at one of their ends, is made up of two coaxial tubular parts (12, 13), conically fitting into each another, each of said parts showing a central passage for the continuously travelling product, and both parts defining between them, for the introduction of water, an annular chamber (20) extending into an annular slit (23) provided between two frusto-conical bearings of the tubular parts, respectively male (15) and female (16) respectively provided on inner tubular part (12) and in outer tubular part (13), said slit having adjustable length and width by axial sliding of inner part (12) in outer part (13), a device in which, with respect to the direction of continuous running of the product to be cooled, the outer part (13) provided with the female frusto-conical bearing (16) is connected to the downstream tube (2), the inner part (12) provided with the male frusto-conical bearing (15), being connected to the upstream tube (4) so that is obtained, on the one hand, in downstream tube (2), a main rate of flow of water in the direction of travelling of the product to be cooled and, on the other hand, in upstream tube (4), a secondary flow of water opposite to said direction, the axial sliding of inner part (12) in outer part (13) being obtained by a cooperation of two sliding bearings and two tightening bearings perpendicularly arranged to the sliding bearings ; one (21) of the sliding bearings being provided on the outer surface of the inner part (12), characterized in that the other sliding bearing (22) is provided on the inner surface of outer part (13), and in that said tightening bearings are made up respectively by an annular ring (25) or (29, 32) provided on inner part (12) and by a shoulder (26) or (26') of outer part (13).

IPC 1-7
B21B 45/02

IPC 8 full level
B21B 45/02 (2006.01); **C21D 9/573** (2006.01)

CPC (source: EP)
B21B 45/0224 (2013.01); **C21D 9/5732** (2013.01)

Cited by
CN104088910A; FR2585368A1; CN115076249A; CN109237046A; ES2109123A1; EP0090682A3; FR2522688A1

Designated contracting state (EPC)
BE DE FR GB IT LU NL

DOCDB simple family (publication)
EP 0020246 A1 19801210; **EP 0020246 B1 19850213**; DE 3070144 D1 19850328; FR 2457724 A1 19801226; FR 2457724 B1 19830513; MY 8600748 A 19861231

DOCDB simple family (application)
EP 80400715 A 19800521; DE 3070144 T 19800521; FR 7914383 A 19790601; MY 8600748 A 19861230