

Title (en)

METHOD OF MAKING AND USING A CERAMIC SHELL MOLD

Publication

**EP 0020373 B1 19830608 (EN)**

Application

**EP 79900983 A 19781204**

Priority

- EP 79900983 A 19781204
- US 7800187 W 19781204

Abstract (en)

[origin: WO8001146A1] A method of making a shell mold (6) includes alternately applying a ceramic coating composition (8) and a stucco composition (10) to an expendable pattern, the presence of graphite being substantially avoided therein, and applying a barrier coating (16) thereto including a ceramic powder, a binder, and a preselected amount of graphite. A preferred range of graphite of about 13 to 17 Wt.% in the barrier coating (16) minimizes decarburization of a ferrous article formed in the cavity of the shell mold (6).

IPC 1-7

**B22C 1/04; B22C 3/00; B22C 9/04; C04B 35/00**

IPC 8 full level

**B22C 1/04** (2006.01); **B22C 1/16** (2006.01); **B22C 3/00** (2006.01); **B22C 9/00** (2006.01); **B22C 9/04** (2006.01); **C04B 35/00** (2006.01)

CPC (source: EP)

**B22C 1/165** (2013.01)

Cited by

US5617912A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**WO 8001146 A1 19800612**; CA 1119771 A 19820316; DE 2862282 D1 19830714; EP 0020373 A1 19810107; EP 0020373 A4 19800929; EP 0020373 B1 19830608; JP S55500934 A 19801113

DOCDB simple family (application)

**US 7800187 W 19781204**; CA 336269 A 19790925; DE 2862282 T 19781204; EP 79900983 A 19781204; JP 50131178 A 19781204