

Title (en)

PREPARATION MACHINE FOR SPINNING

Publication

EP 0022472 B1 19830608 (DE)

Application

EP 80103176 A 19800607

Priority

CH 640779 A 19790704

Abstract (en)

[origin: US4346500A] The converging space between the moving-in or inbound surface of a loosening roll and the surface of a feed roll contains a suction duct, which is brought into close vicinity of the fibre loosening zone located between the two rolls, and which is used for sucking off of dust released in this zone. The suction duct is supported by the body forming the fibre feeder trough. Detrimental deposits of impurities in the subsequent processes, e.g. in the open-end spinning rotors, thus are greatly reduced.

IPC 1-7

D01G 15/80; D01G 15/20

IPC 8 full level

D01G 15/42 (2006.01); **D01G 15/20** (2006.01); **D01G 15/80** (2006.01)

CPC (source: EP US)

D01G 15/20 (2013.01 - EP US); **D01G 15/805** (2013.01 - EP US)

Cited by

FR2760245A1; DE3429024A1; GB2151668A; EP0354426A1; DE3827520A1; US5038439A

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0022472 A1 19810121; EP 0022472 B1 19830608; AT E3727 T1 19830615; DE 3063671 D1 19830714; IN 152630 B 19840225;
JP H0227445 B2 19900618; JP S569429 A 19810130; US 4346500 A 19820831

DOCDB simple family (application)

EP 80103176 A 19800607; AT 80103176 T 19800607; DE 3063671 T 19800607; IN 681CA1980 A 19800610; JP 9006280 A 19800703;
US 15966980 A 19800616