

Title (en)
BRIDGE BEARING

Publication
EP 0022665 B1 19860219 (EN)

Application
EP 80302352 A 19800710

Priority
GB 7924809 A 19790717

Abstract (en)
[origin: EP0022665A1] A bridge bearing comprises a plurality of elements (1, 2, 3) each comprising at least one metal plate (4, 11, 20) at least one of the elements (2) having a layer of rubber (10) disposed between two of the metal plates (11), each metal plate (4, 11, 20) having a single recess (31, 32 or 33) of a shape which is acircular in plan view formed therein, the elements being arranged in a stack, each pair of adjacent metal plates of adjacent elements being restrained from relative rotation about a vertical axis by a key (40) located in the recesses of those plates, the layer(s) of rubber being for absorbing relative rotational movement about a horizontal axis between the top and bottom of the stack. The key or each of the keys and the recesses are preferably cruciform in the shape. If any key were omitted during assembly of the bearing the bearing would fail immediately upon attempted use. The bearing could not function satisfactorily for a short time before failing.

IPC 1-7
E01D 19/04

IPC 8 full level
E01D 19/04 (2006.01); **E04B 1/36** (2006.01); **E01D 101/40** (2006.01)

CPC (source: EP)
E01D 19/041 (2013.01)

Cited by
EP0107933A1; DE19543519A1; CN102094387A; US6770374B1; US7223457B1; US6790537B1

Designated contracting state (EPC)
AT BE CH DE FR IT LI LU NL SE

DOCDB simple family (publication)
EP 0022665 A1 19810121; EP 0022665 B1 19860219; AT E18079 T1 19860315; AU 543027 B2 19850328; AU 6048180 A 19810122;
DE 3071429 D1 19860327; GB 2054092 A 19810211; GB 2054092 B 19830407; JP S5620207 A 19810225; ZA 804283 B 19810729

DOCDB simple family (application)
EP 80302352 A 19800710; AT 80302352 T 19800710; AU 6048180 A 19800717; DE 3071429 T 19800710; GB 7924809 A 19790717;
JP 9861180 A 19800716; ZA 804283 A 19800716