

Title (en)

LAMPHOLDER WITH ARRANGEMENT TO PREVENT ACCESS TO LIVE WIRES

Publication

**EP 0027244 B1 19850206 (DE)**

Application

**EP 80106075 A 19801007**

Priority

CH 911979 A 19791010

Abstract (en)

[origin: EP0027244A1] The device is provided with lead current terminals and a contact arrangement (6, 7) arranged on a support (5). The contact arrangement comprises switching members with two cut off gaps. Each switching member is provided with at least two contact pieces (35, 36, 37; 55, 56, 57) displaceable one towards the other under the action of an outer force so as to close the cut off spaces. The switching members are locked mechanically and/or electrically with respect to each other so as to prevent the conduction of current during touching.

IPC 1-7

**H01R 33/96**

IPC 8 full level

**H01R 33/22** (2006.01); **H01R 33/96** (2006.01)

CPC (source: EP)

**H01R 33/22** (2013.01); **H01R 33/962** (2013.01)

Citation (examination)

DE 1539415 B2 19781012

Cited by

EP0295016A3; US6491534B1; EP1050936A1; EP2797177A4; EP0744792A3; GB2170662A; US4707042A; WO0067349A1; WO2007098758A1; WO02084814A1; WO8505740A1

Designated contracting state (EPC)

AT BE DE FR GB IT LU NL SE

DOCDB simple family (publication)

**EP 0027244 A1 19810422; EP 0027244 B1 19850206**; AT E11716 T1 19850215; CH 648699 A5 19850329; DE 3070121 D1 19850321; DK 428680 A 19810411; WO 8101082 A1 19810416

DOCDB simple family (application)

**EP 80106075 A 19801007**; AT 80106075 T 19801007; CH 8000124 W 19801010; CH 911979 A 19791010; DE 3070121 T 19801007; DK 428680 A 19801010