

Title (en)

Cutting apparatus for an intermittently movable web.

Title (de)

Schneidvorrichtung für eine schrittweise transportierbare Materialbahn.

Title (fr)

Appareil de découpe pour bande transportable par intermittance.

Publication

EP 0029122 A1 19810527 (DE)

Application

EP 80106270 A 19801015

Priority

DE 2945453 A 19791110

Abstract (en)

1. Cutting device for web of material transportable stepwise, cut in its stationary state and guided only in the direction of the normal towards the cutting edge of a cutting bar with a cutting wheel (4) executing a reciprocating movement along the cutting edge (7), which in at least one direction of movement can selectively be activated into a cutting position and which is rotatably arranged on an axle (3) mounted on a carriage (33), and with a roller arranged on the same axle (3) and rolling on the web of material to be cut off, the roller serving in its cutting position as driving roller (8) for the cutting wheel (4), characterized in that the surface (9) of the driving roller (8) is a cylindrical circumferential surface which rolls on the web of material placed on the cutting bar (7), that in this process the common axle (3) supporting driving roller (8) and cutting wheel (4) is arranged obliquely at approximately 3 degrees to approximately 5 degrees to the normal of the cutting edge extending in the direction of the web of material, and that during the cutting process the circumferential speed of the edge of the cutting wheel (4) is approximately 15 to 17 % higher than the circumferential speed of the circumferential surface of the driving roller (8).

Abstract (de)

In einer Schneidvorrichtung für einen Drucker mit schrittweise transportierbarer Papierbahn ist ein hin und her fahrbares Schneidrad (4) vorgesehen, das fest mit einer auf der Papierbahn abrollenden Antriebsrolle (8) verbunden ist, die durch die Schrägstellung der gemeinsamen Achse (3) um etwa 3 bis etwa 5° an Stelle einer sonst erforderlichen Niederhaltung die Papierbahn festhält und spannt. Wichtig ist dabei, daß der Durchmesser des Schneidrades erheblich größer ist als der Durchmesser der Antriebsrolle.

IPC 1-7

B26D 1/20

IPC 8 full level

B26D 1/20 (2006.01); **B26D 5/02** (2006.01); **B41J 11/70** (2006.01)

CPC (source: EP)

B26D 1/205 (2013.01); **B26D 5/02** (2013.01); **B41J 11/706** (2013.01)

Citation (search report)

- DE 2343858 A1 19750320 - NIXDORF COMPUTER AG [DE], et al
- FR 2242250 A1 19750328 - NIXDORF COMPUTER AG [DE]
- US 1960175 A 19340522 - STEVENS ROSWELL C
- FR 2389300 A7 19781124 - ADLERWERKE KLEYER AG H [DE]

Cited by

EP0196580A3; US5819618A; GB2213756A; GB2213756B; EP0172319A1; US4665787A; FR2687607A1; US6423233B1; US6706192B2

Designated contracting state (EPC)

DE FR GB SE

DOCDB simple family (publication)

EP 0029122 A1 19810527; **EP 0029122 B1 19830629**; DE 3063986 D1 19830804

DOCDB simple family (application)

EP 80106270 A 19801015; DE 3063986 T 19801015