

Title (en)

Device for generating a directed current of a gaeous medium.

Title (de)

Vorrichtung zur Erzeugung einer gerichteten Strömung eines gasförmigen Mediums.

Title (fr)

Dispositif pour générer un courant orienté d'un milieu gazeux.

Publication

**EP 0029421 A1 19810527 (DE)**

Application

**EP 80890014 A 19800204**

Priority

AT 738479 A 19791120

Abstract (en)

1. Device for generating a directed current of a gaseous medium, utilizing the electric wind, a discharge electrode 1 being provided for the purpose of forming gas ions and having a high electrical voltage compared with a counter-electrode 3, in order to ensure a discharge current at atmospheric pressures in the range of the Townsend discharge or glow discharge, so that the ions move in a preselected direction 5 or in a preselected sector, with an aperture angle of less than 180 degrees of the imaginary spherical sectors around the emission points of the discharge electrode 1, characterised by the fact that the discharge electrode 1 takes the form of a wire, that corresponding to each discharge electrode there are at least two mutually parallel counter-electrodes 3 present to one side of the discharge electrode and at an equal distance from the latter, the nearest edge of each one extending parallel to the wire-shaped discharge electrode 1, and that the discharge current is between  $10^{**-6} \text{ A/cm}^{**2}$  and  $10^{**-1} \text{ A/cm}^{**2}$ .

Abstract (de)

Vorrichtung zur Erzeugung einer gerichteten Strömung eines gasförmigen Mediums, z. B. eines Luftstromes unter Ausnützung des elektrischen Windes, wobei zur Bildung der Ionen eine unter hohem elektrischen Feld stehende Elektrode (1'), etwa ein Draht vorgesehen ist, an welchem bei atmosphärischen Drücken im Bereich der Townsidentladung oder der Glimmentladung ein Entladungsstrom zwischen  $10^{<->6} \text{ A/cm}^2$  und  $10^{<->1} \text{ A/cm}^2$ , vorzugsweise zwischen  $10^{<->5} \text{ A/cm}^2$  und  $10^{<->3} \text{ A/cm}^2$ , fließt, eine vorzugsweise aus Leitflächen eines Strömungskanals (3) gebildete Gegenelektrode (2') angeordnet ist, und in bevorzugter Weise die Kanten der Leitflächen im wesentlichen parallel zu den Entladungsdrähten verlaufen, so daß sich die Ionen in eine Richtung (4') oder zumindest in einem Sektor der um die Emissionspunkte der Entladungselektrode (1') gedachten Kugeln mit einem Öffnungswinkel, der weniger als  $180^\circ$  beträgt, bewegen.

IPC 1-7

**H01J 41/12; H01T 20/02**

IPC 8 full level

**F04F 99/00** (2009.01); **H01J 41/12** (2006.01); **H01T 23/00** (2006.01)

CPC (source: EP)

**H01J 41/12** (2013.01); **H01T 23/00** (2013.01)

Citation (search report)

- [X] US 3638058 A 19720125 - FRITZIUS ROBERT S
- US 3296491 A 19670103 - TOWNSEND BROWN THOMAS

Cited by

DE102019114053A1; AT389414B; EP0657979A1; US5006761A; AU595179B2; WO9219030A1; WO8607500A1

Designated contracting state (EPC)

BE CH DE FR GB IT NL SE

DOCDB simple family (publication)

**EP 0029421 A1 19810527; EP 0029421 B1 19860820**; DE 3071704 D1 19860925; JP S5676000 A 19810623

DOCDB simple family (application)

**EP 80890014 A 19800204**; DE 3071704 T 19800204; JP 10722780 A 19800806