

Title (en)

## VARIABLE RESONATORS FOR NOISE ATTENUATION

Publication

**EP 0029898 A3 19810826 (DE)**

Application

**EP 80106229 A 19801014**

Priority

DE 2947026 A 19791122

Abstract (en)

[origin: US4325461A] A noise reducing resonator, herein referred to as a silator due to its noise silencing quality, is made up of primary struts forming a main frame and secondary struts forming at least one subframe enclosed by a vacuum tight cover to enclose a vaulting evacuated volume. Each frame has a given span width and a vaulting height corresponding to 0.005 to 0.05 times the respective span width. The frames are arranged in a hierachic order which means that a larger main frame holds a smaller subframe which in turn holds a still smaller subframe and so on. The resonance frequency increases with the number of subframes held in a main frame. Interconnected silators may cover entire surface areas for noise reduction or absorption.

IPC 1-7

**G10K 11/16**

IPC 8 full level

**G10K 11/16** (2006.01); **G10K 11/172** (2006.01)

CPC (source: EP US)

**G10K 11/172** (2013.01 - EP US)

Citation (search report)

US 3773141 A 19731120 - THIEN G, et al

Cited by

CN102951795A

Designated contracting state (EPC)

AT CH FR GB IT NL

DOCDB simple family (publication)

**US 4325461 A 19820420**; AT E13232 T1 19850515; DE 2947026 B1 19801127; DE 2947026 C2 19811001; EP 0029898 A2 19810610;  
EP 0029898 A3 19810826; EP 0029898 B1 19850508

DOCDB simple family (application)

**US 20592280 A 19801112**; AT 80106229 T 19801014; DE 2947026 A 19791122; EP 80106229 A 19801014