

Title (en)

METHOD OF REDUCING THE FRICTION IN THE WET STEPS OF LEATHER MANUFACTURE

Publication

**EP 0029906 B1 19821229 (DE)**

Application

**EP 80106296 A 19801016**

Priority

DE 2942858 A 19791024

Abstract (en)

[origin: EP0029906A1] 1. A process for reducing friction in wet processes of leather production, by the addition of a lubricant, wherein the lubricant employed is from 0.05 to 2 g, per liter of liquor, of a water-soluble polymer having a Fikentscher K value of >150.

IPC 1-7

**C14C 1/00**; **C14C 3/00**

IPC 8 full level

**C14C 1/00** (2006.01); **C14C 3/00** (2006.01)

CPC (source: EP)

**C14C 1/00** (2013.01); **C14C 3/00** (2013.01)

Cited by

US4750906A

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0029906 A1 19810610**; **EP 0029906 B1 19821229**; AT E2153 T1 19830115; AU 6362380 A 19810430; DE 2942858 B1 19810319; DE 3061516 D1 19830203; JP S5667400 A 19810606

DOCDB simple family (application)

**EP 80106296 A 19801016**; AT 80106296 T 19801016; AU 6362380 A 19801023; DE 2942858 A 19791024; DE 3061516 T 19801016; JP 14825180 A 19801024