

Title (en)
FUEL INJECTION DEVICE

Publication
EP 0030979 B1 19860129 (FR)

Application
EP 80901125 A 19810112

Priority
JP 8060579 A 19790625

Abstract (en)
[origin: WO8100020A1] A fuel injection device of the type for correcting an air/fuel ratio by controlling the flow rate of a fuel metering gate disposed in a fuel supply passage with air flow detecting means for detecting the air flow intaken into an engine and by controlling fuel amount with a solenoid valve which is opened or closed by a detection signal indicative of the operating state of the engine. A second solenoid valve is disposed in parallel with the above solenoid valve and is opened or closed by the signal to correct the basic air/fuel ratio set by the relationship between the air flow detecting means and the fuel metering gate, thereby maintaining the air/fuel ratio at desired constant value.

IPC 1-7
F02D 41/00; F02D 3/02; F02M 51/02; F02M 69/00

IPC 8 full level
F02D 35/00 (2006.01); **F02D 41/14** (2006.01); **F02D 41/18** (2006.01); **F02D 41/34** (2006.01); **F02M 69/22** (2006.01); **F02M 69/52** (2006.01)

CPC (source: EP US)
F02D 35/0092 (2013.01 - EP US); **F02D 41/1474** (2013.01 - EP US); **F02D 41/182** (2013.01 - EP US); **F02M 69/22** (2013.01 - EP US)

Designated contracting state (EPC)
FR

DOCDB simple family (publication)
GB 2064650 A 19810617; **GB 2064650 B 19830420**; DE 3049662 C2 19850321; DE 3049662 T1 19820225; EP 0030979 A1 19810701; EP 0030979 A4 19811210; EP 0030979 B1 19860129; JP S566031 A 19810122; US 4373490 A 19830215; WO 8100020 A1 19810108

DOCDB simple family (application)
GB 8100051 A 19800620; DE 3049662 T 19800620; EP 80901125 A 19810112; JP 8000140 W 19800620; JP 8060579 A 19790625; US 22511181 A 19810114