

Title (en)

FUEL-INJECTION DEVICE FOR INTERNAL COMBUSTION ENGINES, ESPECIALLY FOR DIESEL ENGINES

Publication

EP 0032168 B1 19841128 (DE)

Application

EP 80106901 A 19801108

Priority

DE 3001051 A 19800112

Abstract (en)

[origin: EP0032168A1] 1. Fuel injection device for internal combustion machines, in particular for diesel engines, having, for each working cylinder, one mechanically driven pump piston (14a-14d; 14a'-14d') of an injection pump (12a-12d) supplied by a feed pump (33) with fuel under supply pressure, having, for each working cylinder, a control spool valve (24; 24') operable by the control pressure of a control fuel source (32) common to all the injection pumps, which control spool valve is inserted in a transfer duct (22) continually connected with the pump working space (18) and closes this duct for the initiation of the beginning of injection and opens it again for the termination of injection, and having a control device (48; 48'; 48'') by means of which the control pressure can be switched via control lines (29) to the pressure spaces (28) of the control spool valves (24; 24'), characterised by the following features : a) the control fuel source (32) is formed by the feed pump (33) designed for a control pressure (ps) increased by a multiple relative to the supply pressure (pv) of the injection pumps (12a to 12d) and by a first pressure limiting valve (35) limiting the control pressure (ps) in a control pressure line (31) which can be connected to the control lines (29) ; b) a second pressure limiting valve (37), which determines the supply pressure (pv) occurring in the filling lines (21) separated from the control lines (29), is connected downstream of the first pressure limiting valve (35) ; c) the control device consists of a valve arrangement (36; 48; 48'; 48'') determining in common for all the injection pumps (12a to 12d) the beginning and the duration of the period during which the pressure spaces (28) of the control spool valve (24; 24') are subjected to pressure and of a distributor device (43; 53) separate from this valve arrangement, by means of which distributor device one of the control lines (29) leading to the pressure spaces (28) of the control spool valves (24; 24') can be connected at a time, in synchronism with the injections, to the control pressure line (31) ; d) the control pressure (ps) necessary for operating the control spool valve (24; 24') and to which one of the pressure spaces (28) at a time is subjected via the distributor device (43; 53) is built up by the valve arrangement (36; 48; 48'; 48'') blocking the drainage of the control fuel from the control pressure line (31) into a low pressure line (19) and is released again to the low pressure line (19) for the return stroke of the control spool valve (24; 24').

IPC 1-7

F02M 59/36

IPC 8 full level

F02M 57/02 (2006.01); **F02M 55/00** (2006.01); **F02M 59/36** (2006.01); **F02B 3/06** (2006.01)

CPC (source: EP)

F02M 59/362 (2013.01); **F02M 59/365** (2013.01); **F02M 59/366** (2013.01); **F02B 3/06** (2013.01)

Citation (examination)

- US 2069744 A 19370209 - ALDEN CARROLL R
- FR 2235276 A2 19750124 - BENDIX CORP [US]
- DE 920881 C 19541202 - DAIMLER BENZ AG
- DE 594336 C 19340315 - MAGNETI MARELLI SPA
- US 2357563 A 19440905 - TRUXELL JR CLYDE W
- EP 0032171 A1 19810722 - BOSCH GMBH ROBERT [DE]
- EP 0032172 A1 19810722 - BOSCH GMBH ROBERT [DE]
- US 3486493 A 19691230 - DREISIN ALEXANDER

Cited by

FR2508107A1; CN108730085A; NL1014518C2; WO0171180A1; EP0077716B1

Designated contracting state (EPC)

AT DE FR GB IT

DOCDB simple family (publication)

EP 0032168 A1 19810722; EP 0032168 B1 19841128; AT E10532 T1 19841215; DE 3001051 A1 19810716; DE 3069719 D1 19850110; JP H0346664 B2 19910716; JP S56106060 A 19810824

DOCDB simple family (application)

EP 80106901 A 19801108; AT 80106901 T 19801108; DE 3001051 A 19800112; DE 3069719 T 19801108; JP 220681 A 19810112