

Title (en)

ROTARY DRILL BITS

Publication

**EP 0032428 B1 19860827 (EN)**

Application

**EP 81300062 A 19810108**

Priority

GB 8000606 A 19800110

Abstract (en)

[origin: EP0032428A1] In a rotary drilling bit having preform cutting elements, a partial or total structural discontinuity is disposed between the elements and the underlying structure or within the underlying structure to reduce the bending strain upon the preform cutting elements. In this way there is a reduction in the fracture or damage of preform cutting elements.

IPC 1-7

**E21B 10/46; E21B 10/62**

IPC 8 full level

**E21B 10/56** (2006.01); **E21B 10/573** (2006.01); **E21B 10/62** (2006.01)

CPC (source: EP)

**E21B 10/573** (2013.01); **E21B 10/62** (2013.01)

Citation (examination)

- FR 1340987 A 19631025 - TURBODRILL INTERNAT CORP
- US 3697137 A 19721010 - KREKELER CLAUDE B
- US 3168925 A 19650209 - GAYLEY HARRY B
- US 4108260 A 19780822 - BOZARTH REX O
- US 3311181 A 19670328 - FOWLER JOHN B
- US 3771612 A 19731113 - ADCOCK G
- US 4148368 A 19790410 - EVANS ROBERT F
- US 3717209 A 19730220 - SHELDON G, et al
- GB 683018 A 19521119 - SANDVIKENS JERNVERKS AB
- US 2889138 A 19590602 - WILHELM HAGLUND DIDRIK
- US 3362489 A 19680109 - WILLIAM MILLER ROBERT
- US 3745623 A 19730717 - WENTORF R, et al
- US 4156329 A 19790529 - DANIELS WILLIAM H [US], et al
- US 4199035 A 19800422 - THOMPSON DONALD A [US]

Cited by

US4542943A; EP0145422A3; EP0144222A3; EP0511200A1; EP0534370A1; US6009963A; EP0853184A3; FR2524916A1; AT388581B; GB2279677A; US5421425A; GB2279677B; EP0145423A3; US4679639A; GB2409474A; GB2423322A; GB2409474B; GB2423322B; EP0573135A1; US5423719A; EP0326176A3; US7426969B2

Designated contracting state (EPC)

BE CH DE FR GB LI NL SE

DOCDB simple family (publication)

**EP 0032428 A1 19810722; EP 0032428 B1 19860827**; AU 547017 B2 19851003; AU 6618681 A 19810716; DE 3175194 D1 19861002

DOCDB simple family (application)

**EP 81300062 A 19810108**; AU 6618681 A 19810113; DE 3175194 T 19810108