Title (en)

MÉTHOD FOR CHANGING THE CROSS-SECTIONAL FORMAT OF A STRAND IN CONTINUOUS CASTING AND ARRANGEMENT FOR CARRYING OUT SAME

Publication

EP 0033311 A3 19810819 (DE)

Application

EP 81890006 A 19810116

Priority

AT 41680 A 19800125

Abstract (en)

[origin: EP0033311A2] To change the cross-sectional format, the mould (1) used has at least one side wall which can be adjusted relative to an opposite side wall (4) of the mould. In order to be able to change the format (7) without interrupting moulding and using moulds of conventional design, the following procedure is adopted: - during an interruption of moulding, a spontaneous drop in the casting level is awaited and then the following successive steps performed - the slag on the end face of the strand is removed; - one side wall (3) of the mould is shifted outwards; - a sealing body, preferably a pocket-shaped metal sheet (17), is introduced into the space (16) between the shifted side wall (3) of the mould and the strand (8), which sealing body is hooked into the upper edge of the strand shell and - after the provision of cooling scrap (20) on the sealing body, casting is continued.

IPC 1-7

B22D 11/04

IPC 8 full level

B22D 11/04 (2006.01); B22D 11/05 (2006.01)

CPC (source: EP)

B22D 11/05 (2013.01)

Citation (search report)

- DE 2550012 A1 19760513 NIPPON STEEL CORP
- [P] DE 2841656 A1 19800403 SCHLOEMANN SIEMAG AG
- [AP] DE 2903245 A1 19800807 SUMITOMO METAL IND
- [AD] DE 2018962 A1 19711104

Cited by

US4441543A; AT406745B

Designated contracting state (EPC)

BE CH DE FR GB IT LU NL SE

DOCDB simple family (publication)

EP 0033311 A2 19810805; EP 0033311 A3 19810819; AT 364105 B 19810925; AT A41680 A 19810215; JP S56105847 A 19810822

DOCDB simple family (application)

EP 81890006 A 19810116; AT 41680 A 19800125; JP 522181 A 19810119