

Title (en)
AN ALTERNATING CURRENT SOCKET-OUTLET FOR ELECTRIC EQUIPMENT

Publication
EP 0033411 B1 19840530 (EN)

Application
EP 80303289 A 19800918

Priority
JP 391180 U 19800117

Abstract (en)
[origin: EP0033411A2] An alternating current socket-outlet for electric equipments having a body member (10) fixed to a stationary system, a pair of connector members (20), a pair of shutter members (40a, 40b) movable between a first position to cover the connector members and a second position to uncover the connector member, an elastic member (30) urging the shutter members to the first position, and a front cover (50) to guide a pair of the pins (60) of a plug (200) adapted to engage the connector members (20). In order to prevent an electric shock or fire accident, etc., the electric outlets covered by the shutter members (40a and 40b) are uncovered only when the two symmetric, equivalent pushing forces are applied to the shutter members.

IPC 1-7
H01R 13/453

IPC 8 full level
H01R 13/453 (2006.01); **H01R 13/74** (2006.01); **H01R 25/00** (2006.01)

CPC (source: EP)
H01R 13/453 (2013.01); **H01R 13/4534** (2013.01); **H01R 13/74** (2013.01); **H01R 25/006** (2013.01)

Cited by
EP1947741A3; EP0771051A1; FR2740270A1; US5069630A; GB2233509A; GB2233509B; ES2147706A1; EP0053520A3; US4493517A; WO2019129352A1

Designated contracting state (EPC)
DE GB NL SE

DOCDB simple family (publication)
EP 0033411 A2 19810812; EP 0033411 A3 19810909; EP 0033411 B1 19840530; DE 3068044 D1 19840705; JP S56106382 U 19810819; JP S5924140 Y2 19840717

DOCDB simple family (application)
EP 80303289 A 19800918; DE 3068044 T 19800918; JP 391180 U 19800117