

Title (en)

EDGE GRINDING MACHINE FOR PLATE-SHAPED WORKPIECES, PARTICULARLY PLATES OF GLASS OR STONE

Publication

EP 0033922 B1 19831005 (DE)

Application

EP 81100704 A 19810131

Priority

IT 1512580 A 19800208

Abstract (en)

[origin: EP0033922A2] 1. An edge grinding machine for plate-shaped workpieces, particularly plates of glass or stone or the like, comprising a gripping means for gripping the workpiece which is to be machined and which is disposed in a horizontal position with in particular edge portions thereof projecting freely on all sides, said gripping means being disposed on the upper end of a support (A) and comprising in particular a plurality of horizontally disposed suction grippers (C), a cantilever arm which is disposed horizontally radially with respect to the support (A) and which is rotatable around the support in particular through a full 360 degrees, and a grinding unit (1) which is guided displaceably by means of a carriage or the like on the cantilever arm, from and towards the workpiece, and which comprises a grinding wheel (M) which in particular is of a cup-shaped, annular or plate-shaped configuration and which is somewhat inclined with its underneath head surface relative to the plane of the workpiece and which can be pressed against the edge of the workpiece from above, a counter-pressure roller (R2) which is arranged in the region of the grinding wheel on the underside of the workpiece, a guide roller which bears laterally against the peripheral surface of the workpiece, and a drive motor for the grinding wheel, characterised in that the grinding unit (1) is secured to an intermediate holder (34) in such a way as to be pivotal and lockable about a horizontal pivot axis (29) extending parallel to the cantilever arm (E), that is to say, radially with respect to the workpiece (D), by means of a first arcuate guide (28, 30), which intermediate holder (34) is mounted on the carriage (F) which is displaceable in the longitudinal direction of the cantilever arm (E), in such a way as to be pivotal and lockable about a horizontal pivot axis (129) directed transversely with respect to the cantilever arm (E), that is to say, tangentially with respect to the workpiece (D), by means of a second arcuate guide (35, 36), wherein the grinding wheel (M) is secured to the lower end of a vertical grinding spindle (6) which is drivable by a hydraulic motor (10) and which is displaceable upwardly and downwardly in the grinding unit (1) by manual actuating means (16), and the downward stroke movement of the grinding spindle (6) is restricted by at least one adjustable abutment (19).

IPC 1-7

B24B 9/10

IPC 8 full level

B24B 9/10 (2006.01); **B24B 27/00** (2006.01)

CPC (source: EP)

B24B 9/10 (2013.01); **B24B 27/0084** (2013.01)

Cited by

EP0451333A3; CN107378734A; DE3625535C1; CN104907840A; EP0703039A1; CN116423331A; ES2143347A1; US5185959A; EP0424815A1; CN104400598A

Designated contracting state (EPC)

AT BE CH DE FR GB LI LU NL SE

DOCDB simple family (publication)

EP 0033922 A2 19810819; EP 0033922 A3 19820310; EP 0033922 B1 19831005; AT E4872 T1 19831015; DE 3161060 D1 19831110

DOCDB simple family (application)

EP 81100704 A 19810131; AT 81100704 T 19810131; DE 3161060 T 19810131