

Title (en)
ASYMMETRICAL BUSBAR SYSTEM FOR ELECTROLYSIS CELLS

Publication
EP 0034117 A3 19810826 (DE)

Application
EP 81810017 A 19810123

Priority
CH 81380 A 19800201

Abstract (en)
[origin: US4261807A] Longitudinally arranged electrolytic cells for the production of aluminum in particular, incur high investment and operating costs due to the arrangement of the busbars outside the cells. These busbars induce magnetic fields which in turn cause stirring effects in the metal in the cell. If at least the last cathode bar ends (in terms of the direction of flow I of current) on both sides of the cell are connected via busbars to the end of the anode beam at the current ingoing end of the next cell or the other end of the anode beam, this gives rise to an asymmetry which eliminates the harmful effects of the magnetic fields and helps to lower the investment and operational costs.

IPC 1-7
C25C 3/16

IPC 8 full level
C25C 3/16 (2006.01)

CPC (source: EP US)
C25C 3/16 (2013.01 - EP US)

Citation (search report)
FR 2105172 A1 19720428 - ALUSUISSE

Designated contracting state (EPC)
AT CH DE FR GB IT NL SE

DOCDB simple family (publication)
US 4261807 A 19810414; AR 225489 A1 19820331; AU 6651881 A 19810806; BR 8100591 A 19810818; DE 3009096 A1 19810806; EP 0034117 A2 19810819; EP 0034117 A3 19810826; ZA 81280 B 19820224

DOCDB simple family (application)
US 13239780 A 19800320; AR 28417881 A 19810202; AU 6651881 A 19810121; BR 8100591 A 19810202; DE 3009096 A 19800310; EP 81810017 A 19810123; ZA 81280 A 19810116