

Title (en)  
Frame.

Title (de)  
Feststehender Rahmen.

Title (fr)  
Chambranle.

Publication  
**EP 0036686 A1 19810930 (FR)**

Application  
**EP 81200274 A 19810312**

Priority  
LU 82275 A 19800320

Abstract (en)  
1. Casing for lining door or window openings (4) provided in a wall (27), said casing being essentially comprised for each one of the sides (1, 2, 3) from the opening (4), of a set of at least two angle-shaped elements (5 and 6, or 7 and 8) each having two legs (5', 5'', 6', 6'', 7', 7'', 8', 8'') at right angle, an inner leg (5', 6', 7', 8') extending inside the opening (4) facing and adjacent the one side (1, 2, or 3) from this latter one, and an outer leg (5'', 6'', 7'', 8'') extending outside the opening (4) along the wall (27), in such a way as to cover the edges (9 and 10) of the opening (4), the inner legs (5' and 6', or 7' and 8') from one and the same element set (5 and 6, or 7 and 8) being joined together by a covering part (13) simultaneously mounted against the surface from said inner legs (5' and 6', or 7' and 8') opposite to the one facing the side (1, 2 or 3) adjacent to which said legs (5' and 6', or 7' and 8') are laid, a connecting mechanism (11) being provided between said side (1, 2, or 3) and the inner legs (5', 6', 7', 8') to fasten same to the corresponding side, said casing being characterized in that said connecting mechanism (11) comprises on the one hand a fastening support (12) mounted on the inner leg (5', 7') of the element (5, 7) having been laid first and projecting slightly relative to said latter leg into the opening (4) while forming also a bearing for the leg (6', 8') of the other element (6, 8) from the set, and on the other hand means (18, 19, 20, 21, 22) for mounting said fastening support (12) on said side (1, 2, 3) and for adjusting and locking the position of said latter support and the element (5, 7) relative to the side (1, 2, 3) of the opening (4), as well as means (43) for fastening the inner leg (6', 8') of the element (6, 8) laid last on the portion from the support (12) projecting partly from the inner leg (5', 7') of the element (5, 7).

Abstract (fr)  
Pour chacun des bords (1 et 2) d'une baie (4) à garnir, un ensemble d'au moins deux éléments (5 et 6 ou 7 et 8) assemblés et montés dans la baie (4) en adaptant successivement un des deux éléments (5 ou 7) d'un même ensemble sur une des arêtes (9) d'un bord déterminé (1 et 3) de la baie (4), et l'autre élément (6 ou 8) sur l'arête opposée (10) de ce même bord, des pièces de liaison (11) étant prévues pour être fixées au dos de l'élément (5 ou 7) de l'ensemble destiné à être posé en premier lieu dans la baie (4), ces pièces présentant une partie (12) dépassant latéralement de cet élément (5 ou 7) pour pouvoir servir de support à l'autre élément (6 ou 8) du même ensemble se fixant également par son dos à cette partie, ces deux éléments ainsi fixés se joignant à l'intérieur de la baie (4) par l'intermédiaire d'une pièce de recouvrement (13) pouvant être posée simultanément sur la face avant des deux éléments.

IPC 1-7  
**E06B 1/18**; **E06B 1/30**

IPC 8 full level  
**E06B 1/18** (2006.01); **E06B 1/20** (2006.01); **E06B 1/30** (2006.01); **E06B 1/60** (2006.01); **E06B 3/988** (2006.01)

CPC (source: EP)  
**E06B 1/20** (2013.01); **E06B 1/603** (2013.01); **E06B 3/988** (2013.01)

Citation (search report)  
BE 694684 A 19670731

Cited by  
FR2561300A1; CN103306577A; EP0621224A3; US5445244A

Designated contracting state (EPC)  
AT BE CH DE FR GB IT NL SE

DOCDB simple family (publication)  
**EP 0036686 A1 19810930**; **EP 0036686 B1 19841128**; AT E10528 T1 19841215; DE 3167377 D1 19850110; LU 82275 A1 19811030

DOCDB simple family (application)  
**EP 81200274 A 19810312**; AT 81200274 T 19810312; DE 3167377 T 19810312; LU 82275 A 19800320