

Title (en)

Device for correcting the position of a plate carried by a cylinder of a printing machine.

Title (de)

Vorrichtung zum Korrigieren des Standes einer durch einen Zylinder einer Druckmaschine getragenen Druckplatte.

Title (fr)

Dispositif pour corriger la position d'une plaque portée par un cylindre d'une machine d'impression.

Publication

**EP 0037754 A1 19811014 (FR)**

Application

**EP 81400386 A 19810313**

Priority

FR 8006317 A 19800321

Abstract (en)

1. Device for correcting the skew of a plate mounted on a plate-holding cylinder of a printing machine, especially an offset printing machine, this cylinder incorporating an inner longitudinal chamber opening radially onto the periphery of the cylinder via a slit into which can be inserted the folded ends of the plate, one of which is applied and retained round a bearing rim provided on one of the edges of the slit, whilst the other is engaged with a retaining means associated with members which, within the chamber, are provided for tensioning the plate, characterised in that the bearing rim can be adjusted angularly by means of a rigid wedge (42) of general prismatic shape, comprising a tapered portion (41) adjacent to the said edge of the slit (6) and two parallel faces (44, 46) engaged with sliding contact in a receptacle (28) adjacent to the chamber (11), in that these faces (44, 46) which define the plane in which the wedge (42) moves form an acute angle with a tangent to the cylinder at the level of the slit (6), and in that at least two threaded rods (82), which are spaced from one another and are screwed into complementary nuts (83) fixed in the cylinder body (2) and the geometrical axis of which passes through the slit (6) of the cylinder, are supported and guided by the adjusting wedge in such a way that by rotating the threaded rods from the slit it is possible to impart to the wedge sliding in its receptacle an inclination which directs the bearing rim along a desired oblique line in relation to the axis (ZZ) of the cylinder.

Abstract (fr)

Pour permettre à la plaque (9) fixée sur le cylindre porte-plaque (1) de prendre une forme hélicoïdale assurant la mise en position correcte du cliché porté par la plaque, l'une des extrémités (7) de la plaque peut être, sur l'une des rives, décalée circonférentiellement, par exemple de la quantité (a) par rapport à l'autre rive, au moyen d'une cale prismatique (42) qui, à l'intérieur de son logement (28), peut prendre une position en dévers sous l'action de vis commandées à partir de la fente (6), de telle sorte qu'une poussée soit appliquée sur la languette élastique (34) qui reçoit en appui l'extrémité (7) de la plaque.

IPC 1-7

**B41F 27/12**

IPC 8 full level

**B41F 27/12** (2006.01)

CPC (source: EP)

**B41F 27/125** (2013.01)

Citation (search report)

- FR 1283031 A 19620127 - MIEHLE GOSS DEXTER INC
- FR 2060840 A5 19710618 - MASCHF AUGSBURG NUERNBERG AG
- FR 2328574 A1 19770520 - MASCHF AUGSBURG NUERNBERG AG [DE]
- FR 1223614 A 19600617 - MARINONI
- GB 635628 A 19500412 - R HOE & CRABTREE LTD
- FR 1523531 A 19680503 - ADAMOVSKA STROJIRNY NP

Cited by

EP0443350A1; US4870901A; GB2287221A; GB2287221B

Designated contracting state (EPC)

CH DE FR GB IT SE

DOCDB simple family (publication)

**EP 0037754 A1 19811014; EP 0037754 B1 19830622**; DE 3160458 D1 19830728; FR 2478538 A1 19810925; FR 2478538 B1 19831007

DOCDB simple family (application)

**EP 81400386 A 19810313**; DE 3160458 T 19810313; FR 8006317 A 19800321