

Title (en)

CHAIN-LINK SUSPENSION FOR RAILWAY VEHICLE

Publication

EP 0038252 B1 19830622 (FR)

Application

EP 81400558 A 19810408

Priority

- FR 8007847 A 19800408
- FR 8020179 A 19800919

Abstract (en)

[origin: EP0038252A1] 1. Pendulous suspension for a railway vehicle body on a carrying axle, where each axle box (5) is firmly fixed to a leaf spring (4), and where the vehicle chassis (7) is suspended at the end of each spring (4) by at least one pair of rings (8, 9) which are retained in bearings in the form of grooves which are combined in links (12, 10, 14), two of the latter (12, 14) being jointed by pins (11, 13) to the end of the spring (4) and to a fixed arm (6) on the chassis (7) respectively, characterised in that at least for one of the load-carrying regions of contact of a ring (8, 9) with a link (12, 10, 14) or of a link (12, 14) with a pin (11, 13), or of a pin (11, 13) with the end of the spring (4) or with the fixed arm (6), contact is made along two lines (A' A'') whose angular separation α , relative to the centre (O) of the load-carrying portion of the ring (8, 9) or of the pin (11, 13), is such that $\tan \alpha/2 > f$, where f is the coefficient of friction between the components in contact.

IPC 1-7

B61F 5/30

IPC 8 full level

B61F 5/30 (2006.01)

CPC (source: EP)

B61F 5/302 (2013.01)

Cited by

CN113501024A; GB2117724A

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0038252 A1 19811021; EP 0038252 B1 19830622; DE 3160467 D1 19830728; ES 501142 A0 19820301; ES 8202741 A1 19820301

DOCDB simple family (application)

EP 81400558 A 19810408; DE 3160467 T 19810408; ES 501142 A 19810407