

Title (en)
APPARATUS FOR APPLYING A COATING LAYER TO A CONTINUOUSLY TRAVELLING WEB

Publication
EP 0038729 B1 19840627 (FR)

Application
EP 81400510 A 19810330

Priority
FR 8008553 A 19800416

Abstract (en)
[origin: ES8202494A1] The coating device of the invention, which enables a layer of product to be deposited on a strip (1) travelling between two rotary cylinders (2, 3), is characterized in that it comprises a reserve (8) containing the coating product a first roller (9) associated with the reserve for continuously taking therefrom a specific amount of coating product a second roller (10) bearing against one of the rotary cylinders (3, 2), the first and second rollers being parallel and spaced from each other a third loosely mounted roller (11), bearing on the first and second rollers means (M1) for rotating the first roller and imparting thereto a constant preadjusted speed and means (M2) for rotating the second roller and imparting thereto a speed equal to the travelling speed of the strip, the first and second rollers rotating in the same direction .

IPC 1-7
B05C 1/08; **B05C 1/04**

IPC 8 full level
B05C 1/04 (2006.01); **B05C 1/08** (2006.01)

CPC (source: EP US)
B05C 1/0834 (2013.01 - EP US); **B05C 1/0865** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0038729 A1 19811028; **EP 0038729 B1 19840627**; AT E8112 T1 19840715; DE 3164393 D1 19840802; ES 501360 A0 19820216; ES 8202494 A1 19820216; FR 2480627 A1 19811023; FR 2480627 B1 19841019; JP S56161858 A 19811212; US 4363288 A 19821214

DOCDB simple family (application)
EP 81400510 A 19810330; AT 81400510 T 19810330; DE 3164393 T 19810330; ES 501360 A 19810414; FR 8008553 A 19800416; JP 5515381 A 19810414; US 24793781 A 19810326