

Title (en)

METHOD AND PRINTING HEAD TO PRODUCE PRINTING SIGNS BY THE MATRIX PRINTING METHOD

Publication

**EP 0041916 A3 19821103 (DE)**

Application

**EP 81730043 A 19810409**

Priority

DE 3022128 A 19800610

Abstract (en)

[origin: US4400101A] The print head of a matrix printer includes two columns of print wires held in separate members which are individually vertically displaceable as well as together in order to obtain different conditions for printing. Good quality or high-speed modes can be obtained in a single pass, high quality in two passes, or a single pass with alternating, vertical displacement of the members for each print position.

IPC 1-7

**B41J 3/10**

IPC 8 full level

**B41J 2/255** (2006.01); **B41J 2/51** (2006.01)

CPC (source: EP US)

**B41J 25/001** (2013.01 - EP US); **B41J 25/005** (2013.01 - EP US)

Citation (search report)

DE 2632293 A1 19770217 - IBM

Cited by

EP0052066B1

Designated contracting state (EPC)

FR GB IT NL

DOCDB simple family (publication)

**EP 0041916 A2 19811216; EP 0041916 A3 19821103; EP 0041916 B1 19860226**; DE 3022128 A1 19811217; DE 3022128 C2 19831208; JP S5727766 A 19820215; US 4400101 A 19830823

DOCDB simple family (application)

**EP 81730043 A 19810409**; DE 3022128 A 19800610; JP 8552881 A 19810603; US 25011781 A 19810402