

Title (en)  
CATCH OR LOCK

Publication  
**EP 0042310 B1 19830601 (EN)**

Application  
**EP 81302756 A 19810618**

Priority  
GB 8019979 A 19800618

Abstract (en)  
[origin: EP0042310A1] A cam (3) is rotatable to move one or two resilient latching arms (20) at the end of which may be latching means (25) engageable on a hasp (4) to catch or lock an article. The cam (3) or casing (1) has a follower (18) which acts in a groove with a ramped bottom dividing the groove into two portions and preventing the cam from being totated from the second back to the first portion. When the cam is in a first position (x) with the follower in the first portion the latching means are held open and are inoperative for latching, the key is then inserted to move the can so the follower is in the second portion, wherein the cam is movable between positions (y) and (z) in which the latching means open and close respectively and wherein the key is removable in position (z).

IPC 1-7  
**E05B 65/52**; **E05C 3/16**; **A47K 10/24**

IPC 8 full level  
**A47K 10/24** (2006.01); **E05B 35/04** (2006.01); **E05B 65/52** (2006.01); **E05C 3/16** (2006.01); **E05C 3/34** (2006.01)

CPC (source: EP)  
**E05C 3/34** (2013.01)

Cited by  
GB2424445A; DE20318465U1; CH703959A1; DE3929041A1; DE3929041C2; US8479956B2; US11447580B2; WO9218733A1

Designated contracting state (EPC)  
AT BE CH DE FR IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0042310 A1 19811223**; **EP 0042310 B1 19830601**; AT E3660 T1 19830615; DE 3160390 D1 19830707; GB 2080396 A 19820203; GB 2080396 B 19840502; NO 154891 B 19860929; NO 154891 C 19870107; NO 812052 L 19811221

DOCDB simple family (application)  
**EP 81302756 A 19810618**; AT 81302756 T 19810618; DE 3160390 T 19810618; GB 8118756 A 19810618; NO 812052 A 19810617