

Title (en)

SURGE VOLTAGE ARRESTER WITH VENTSSAFE FEATURE

Publication

EP 0044894 B1 19850508 (EN)

Application

EP 80302592 A 19800730

Priority

EP 80302592 A 19800730

Abstract (en)

[origin: EP0044894A1] A surge voltage arrester assembly comprises a primary gas tube surge arrester (22) and an air gap secondary arrester that provides surge protection should the gas tube become vented to atmosphere. The secondary arrester has the air gap (42) defined by a rim (45) of one of the gas tube electrodes and an opposed roughened surface (40) of a metallic cup into which the gas tube is positioned. The roughened cup surface has a coating of graphite (43) applied thereto. The electrode rim (45) may or may not be roughened and/or coated. In a three element version of the invention wherein the gas tube has two line electrodes (70, 70) and a ground electrode (72), metallic cups (80, 80) are provided at opposite ends of the gas tube to cooperate with the ground electrode for forming secondary air gaps (86, 86) for each line electrode. The cup surfaces at the secondary air gaps are roughened and graphite (83) coated. An O-ring (88) seals each secondary air gap against the entrance of contaminants.

IPC 1-7

H01T 4/00; H01T 1/14

IPC 8 full level

H01T 1/14 (2006.01)

CPC (source: EP)

H01C 7/12 (2013.01); **H01T 1/14** (2013.01)

Citation (examination)

- US 4208694 A 19800617 - GILBERTS ALEXANDER G [US]
- US 4148089 A 19790403 - KERNS BECKY T, et al
- US 1488936 A 19240401 - PARKER FREDERICK R
- EP 0014543 A1 19800820 - RELIABLE ELECTRIC CO [US]
- DE 2416945 A1 19751009 - SIEMENS AG

Cited by

GB2200243A; GB2200243B; GB2205992A; GB2205992B; EP0060530A1; US7053536B1; WO0039901A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0044894 A1 19820203; EP 0044894 B1 19850508; DE 3070613 D1 19850613

DOCDB simple family (application)

EP 80302592 A 19800730; DE 3070613 T 19800730