

Title (en)

CLOSURE FOR HOLDERS HAVING THICKENED EDGES

Publication

**EP 0045439 B1 19850515 (DE)**

Application

**EP 81105748 A 19810721**

Priority

DE 8020985 U 19800805

Abstract (en)

[origin: US4387826A] A closure device for cans having a beaded edge and a cover with a wall part to be torn-off for formation of a pouring opening, the closure device being provided at two opposite ends of a base body with flanges directed toward each other, which grip under the beaded edge of the can. One of the flanges is elastically deflectable, the other flange is formed rigid, such that the closure device can be pressed onto the can from above like a snap-on-cap. A sealing ring is guided at the base body at the side disposed opposite to the pouring opening such that this sealing ring grips around the exit opening in a compressed state upon placing of the closure device onto the can, the sealing ring being disposed tightly at the cover of the can. Selected FIG. 4.

IPC 1-7

**B65D 39/00; B65D 45/28**

IPC 8 full level

**B65D 39/16** (2006.01); **B65D 39/00** (2006.01); **B65D 39/04** (2006.01); **B65D 43/04** (2006.01); **B65D 43/08** (2006.01); **B65D 45/28** (2006.01);  
**B65D 47/32** (2006.01); **B65D 51/00** (2006.01)

CPC (source: EP US)

**B65D 45/28** (2013.01 - EP US); **B65D 51/007** (2013.01 - EP US)

Cited by

DE3942292A1; DE3425920A1; EP0112306A3

Designated contracting state (EPC)

AT CH DE FR GB IT LI

DOCDB simple family (publication)

**EP 0045439 A2 19820210; EP 0045439 A3 19820602; EP 0045439 B1 19850515;** AT E13274 T1 19850615; DE 3170496 D1 19850620;  
DE 8020985 U1 19810115; JP H0419096 B2 19920330; JP S5755858 A 19820403; US 4387826 A 19830614

DOCDB simple family (application)

**EP 81105748 A 19810721;** AT 81105748 T 19810721; DE 3170496 T 19810721; DE 8020985 U 19800805; JP 12195781 A 19810805;  
US 28870081 A 19810731